

Computer programmers are those who write computer software. In the 1880s, Herman Hollerith invented the concept of storing data in machine-readable form. Also, specific user environment and usage history can make it difficult to reproduce the problem. In 1206, the Arab engineer Al-Jazari invented a programmable drum machine where a musical mechanical automaton could be made to play different rhythms and drum patterns, via pegs and cams. Normally the first step in debugging is to attempt to reproduce the problem. Some text editors such as Emacs allow GDB to be invoked through them, to provide a visual environment. The first compiler related tool, the A-0 System, was developed in 1952 by Grace Hopper, who also coined the term 'compiler'. Many programmers use forms of Agile software development where the various stages of formal software development are more integrated together into short cycles that take a few weeks rather than years. Expert programmers are familiar with a variety of well-established algorithms and their respective complexities and use this knowledge to choose algorithms that are best suited to the circumstances. For example, when a bug in a compiler can make it crash when parsing some large source file, a simplification of the test case that results in only few lines from the original source file can be sufficient to reproduce the same crash. Debugging is often done with IDEs. Standalone debuggers like GDB are also used, and these often provide less of a visual environment, usually using a command line. Debugging is often done with IDEs. Standalone debuggers like GDB are also used, and these often provide less of a visual environment, usually using a command line. Many applications use a mix of several languages in their construction and use. By the late 1960s, data storage devices and computer terminals became inexpensive enough that programs could be created by typing directly into the computers. The first step in most formal software development processes is requirements analysis, followed by testing to determine value modeling, implementation, and failure elimination (debugging). Scripting and breakpointing is also part of this process. Languages form an approximate spectrum from "low-level" to "high-level"; "low-level" languages are typically more machine-oriented and faster to execute, whereas "high-level" languages are more abstract and easier to use but execute less quickly. After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. Ideally, the programming language best suited for the task at hand will be selected. When debugging the problem in a GUI, the programmer can try to skip some user interaction from the original problem description and check if remaining actions are sufficient for bugs to appear. Following a consistent programming style often helps readability. However, readability is more than just programming style. In the 1880s, Herman Hollerith invented the concept of storing data in machine-readable form. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. While these are sometimes considered programming, often the term software development is used for this larger overall process – with the terms programming, implementation, and coding reserved for the writing and editing of code per se.