

Normally the first step in debugging is to attempt to reproduce the problem. Computer programming or coding is the composition of sequences of instructions, called programs, that computers can follow to perform tasks. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. However, Charles Babbage had already written his first program for the Analytical Engine in 1837. A similar technique used for database design is Entity-Relationship Modeling (ER Modeling). As early as the 9th century, a programmable music sequencer was invented by the Persian Banu Musa brothers, who described an automated mechanical flute player in the Book of Ingenious Devices. Debugging is often done with IDEs. Standalone debuggers like GDB are also used, and these often provide less of a visual environment, usually using a command line. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. Whatever the approach to development may be, the final program must satisfy some fundamental properties. It is very difficult to determine what are the most popular modern programming languages. While these are sometimes considered programming, often the term software development is used for this larger overall process – with the terms programming, implementation, and coding reserved for the writing and editing of code per se. In 1801, the Jacquard loom could produce entirely different weaves by changing the "program" – a series of pasteboard cards with holes punched in them. Machine code was the language of early programs, written in the instruction set of the particular machine, often in binary notation. Allen Downey, in his book *How To Think Like A Computer Scientist*, writes: Many computer languages provide a mechanism to call functions provided by shared libraries. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. In the 1880s, Herman Hollerith invented the concept of storing data in machine-readable form. Methods of measuring programming language popularity include: counting the number of job advertisements that mention the language, the number of books sold and courses teaching the language (this overestimates the importance of newer languages), and estimates of the number of existing lines of code written in the language (this underestimates the number of users of business languages such as COBOL). FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. Sometimes software development is known as software engineering, especially when it employs formal methods or follows an engineering design process. Trade-offs from this ideal involve finding enough programmers who know the language to build a team, the availability of compilers for that language, and the efficiency with which programs written in a given language execute. Use of a static code analysis tool can help detect some possible problems. A study found that a few simple readability transformations made code shorter and drastically reduced the time to understand it. Expert programmers are familiar with a variety of well-established algorithms and their respective complexities and use this knowledge to choose algorithms that are best suited to the circumstances. They are the building blocks for all software, from the simplest applications to the most sophisticated ones. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages.