

Languages form an approximate spectrum from "low-level" to "high-level"; "low-level" languages are typically more machine-oriented and faster to execute, whereas "high-level" languages are more abstract and easier to use but execute less quickly. A similar technique used for database design is Entity-Relationship Modeling (ER Modeling). There exist a lot of different approaches for each of those tasks. While these are sometimes considered programming, often the term software development is used for this larger overall process – with the terms programming, implementation, and coding reserved for the writing and editing of code per se. In 1206, the Arab engineer Al-Jazari invented a programmable drum machine where a musical mechanical automaton could be made to play different rhythms and drum patterns, via pegs and cams. After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. Trade-offs from this ideal involve finding enough programmers who know the language to build a team, the availability of compilers for that language, and the efficiency with which programs written in a given language execute. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. There exist a lot of different approaches for each of those tasks. He gave the first description of cryptanalysis by frequency analysis, the earliest code-breaking algorithm. Debugging is a very important task in the software development process since having defects in a program can have significant consequences for its users. After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. In the 9th century, the Arab mathematician Al-Kindi described a cryptographic algorithm for deciphering encrypted code, in A Manuscript on Deciphering Cryptographic Messages. Assembly languages were soon developed that let the programmer specify instruction in a text format (e.g., ADD X, TOTAL), with abbreviations for each operation code and meaningful names for specifying addresses. Compilers harnessed the power of computers to make programming easier by allowing programmers to specify calculations by entering a formula using infix notation. Some languages are very popular for particular kinds of applications, while some languages are regularly used to write many different kinds of applications. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. He gave the first description of cryptanalysis by frequency analysis, the earliest code-breaking algorithm. As early as the 9th century, a programmable music sequencer was invented by the Persian Banu Musa brothers, who described an automated mechanical flute player in the Book of Ingenious Devices. Normally the first step in debugging is to attempt to reproduce the problem. There are many approaches to the Software development process. In the 1880s, Herman Hollerith invented the concept of storing data in machine-readable form. High-level languages made the process of developing a program simpler and more understandable, and less bound to the underlying hardware. Scripting and breakpointing is also part of this process. Ideally, the programming language best suited for the task at hand will be selected.