

Implementation techniques include imperative languages (object-oriented or procedural), functional languages, and logic languages. Compilers harnessed the power of computers to make programming easier by allowing programmers to specify calculations by entering a formula using infix notation. Machine code was the language of early programs, written in the instruction set of the particular machine, often in binary notation. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. These compiled languages allow the programmer to write programs in terms that are syntactically richer, and more capable of abstracting the code, making it easy to target varying machine instruction sets via compilation declarations and heuristics. Programs were mostly entered using punched cards or paper tape. Computer programmers are those who write computer software. Auxiliary tasks accompanying and related to programming include analyzing requirements, testing, debugging (investigating and fixing problems), implementation of build systems, and management of derived artifacts, such as programs' machine code. These compiled languages allow the programmer to write programs in terms that are syntactically richer, and more capable of abstracting the code, making it easy to target varying machine instruction sets via compilation declarations and heuristics. The first step in most formal software development processes is requirements analysis, followed by testing to determine value modeling, implementation, and failure elimination (debugging). Computer programming or coding is the composition of sequences of instructions, called programs, that computers can follow to perform tasks. Debugging is a very important task in the software development process since having defects in a program can have significant consequences for its users. Different programming languages support different styles of programming (called programming paradigms). In the 1880s, Herman Hollerith invented the concept of storing data in machine-readable form. However, Charles Babbage had already written his first program for the Analytical Engine in 1837. The first step in most formal software development processes is requirements analysis, followed by testing to determine value modeling, implementation, and failure elimination (debugging). The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. Allen Downey, in his book *How To Think Like A Computer Scientist*, writes: Many computer languages provide a mechanism to call functions provided by shared libraries. Some text editors such as Emacs allow GDB to be invoked through them, to provide a visual environment. Programmers typically use high-level programming languages that are more easily intelligible to humans than machine code, which is directly executed by the central processing unit. Languages form an approximate spectrum from "low-level" to "high-level"; "low-level" languages are typically more machine-oriented and faster to execute, whereas "high-level" languages are more abstract and easier to use but execute less quickly. In the 9th century, the Arab mathematician Al-Kindi described a cryptographic algorithm for deciphering encrypted code, in *A Manuscript on Deciphering Cryptographic Messages*. The first compiler related tool, the A-0 System, was developed in 1952 by Grace Hopper, who also coined the term 'compiler'. A similar technique used for database design is Entity-Relationship Modeling (ER Modeling). Implementation techniques include imperative languages (object-oriented or procedural), functional languages, and logic languages.