

Many factors, having little or nothing to do with the ability of the computer to efficiently compile and execute the code, contribute to readability. He gave the first description of cryptanalysis by frequency analysis, the earliest code-breaking algorithm. Their jobs usually involve: Although programming has been presented in the media as a somewhat mathematical subject, some research shows that good programmers have strong skills in natural human languages, and that learning to code is similar to learning a foreign language. However, with the concept of the stored-program computer introduced in 1949, both programs and data were stored and manipulated in the same way in computer memory. New languages are generally designed around the syntax of a prior language with new functionality added, (for example C++ adds object-orientation to C, and Java adds memory management and bytecode to C++, but as a result, loses efficiency and the ability for low-level manipulation). Expert programmers are familiar with a variety of well-established algorithms and their respective complexities and use this knowledge to choose algorithms that are best suited to the circumstances. Some text editors such as Emacs allow GDB to be invoked through them, to provide a visual environment. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. Many applications use a mix of several languages in their construction and use. Readability is important because programmers spend the majority of their time reading, trying to understand, reusing and modifying existing source code, rather than writing new source code. Allen Downey, in his book *How To Think Like A Computer Scientist*, writes: Many computer languages provide a mechanism to call functions provided by shared libraries. Scripting and breakpointing is also part of this process. Computer programmers are those who write computer software. It is usually easier to code in "high-level" languages than in "low-level" ones. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. For example, when a bug in a compiler can make it crash when parsing some large source file, a simplification of the test case that results in only few lines from the original source file can be sufficient to reproduce the same crash. Sometimes software development is known as software engineering, especially when it employs formal methods or follows an engineering design process. Some languages are very popular for particular kinds of applications, while some languages are regularly used to write many different kinds of applications. In the 9th century, the Arab mathematician Al-Kindi described a cryptographic algorithm for deciphering encrypted code, in *A Manuscript on Deciphering Cryptographic Messages*. Readability is important because programmers spend the majority of their time reading, trying to understand, reusing and modifying existing source code, rather than writing new source code. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. Assembly languages were soon developed that let the programmer specify instruction in a text format (e.g., ADD X, TOTAL), with abbreviations for each operation code and meaningful names for specifying addresses. They are the building blocks for all software, from the simplest applications to the most sophisticated ones. Assembly languages were soon developed that let the programmer specify instruction in a text format (e.g., ADD X, TOTAL), with abbreviations for each operation code and meaningful names for specifying addresses. Computer programmers are those who write computer software.