

After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. Implementation techniques include imperative languages (object-oriented or procedural), functional languages, and logic languages. Debugging is often done with IDEs. Standalone debuggers like GDB are also used, and these often provide less of a visual environment, usually using a command line. It involves designing and implementing algorithms, step-by-step specifications of procedures, by writing code in one or more programming languages. By the late 1960s, data storage devices and computer terminals became inexpensive enough that programs could be created by typing directly into the computers. Programmers typically use high-level programming languages that are more easily intelligible to humans than machine code, which is directly executed by the central processing unit. Readability is important because programmers spend the majority of their time reading, trying to understand, reusing and modifying existing source code, rather than writing new source code. Computer programming or coding is the composition of sequences of instructions, called programs, that computers can follow to perform tasks. In the 1880s, Herman Hollerith invented the concept of storing data in machine-readable form. They are the building blocks for all software, from the simplest applications to the most sophisticated ones. Many factors, having little or nothing to do with the ability of the computer to efficiently compile and execute the code, contribute to readability. After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. These compiled languages allow the programmer to write programs in terms that are syntactically richer, and more capable of abstracting the code, making it easy to target varying machine instruction sets via compilation declarations and heuristics. They are the building blocks for all software, from the simplest applications to the most sophisticated ones. A study found that a few simple readability transformations made code shorter and drastically reduced the time to understand it. They are the building blocks for all software, from the simplest applications to the most sophisticated ones. Normally the first step in debugging is to attempt to reproduce the problem. Allen Downey, in his book *How To Think Like A Computer Scientist*, writes: Many computer languages provide a mechanism to call functions provided by shared libraries. Provided the functions in a library follow the appropriate run-time conventions (e.g., method of passing arguments), then these functions may be written in any other language. Assembly languages were soon developed that let the programmer specify instruction in a text format (e.g., ADD X, TOTAL), with abbreviations for each operation code and meaningful names for specifying addresses. Languages form an approximate spectrum from "low-level" to "high-level"; "low-level" languages are typically more machine-oriented and faster to execute, whereas "high-level" languages are more abstract and easier to use but execute less quickly. For example, when a bug in a compiler can make it crash when parsing some large source file, a simplification of the test case that results in only few lines from the original source file can be sufficient to reproduce the same crash. Proficient programming usually requires expertise in several different subjects, including knowledge of the application domain, details of programming languages and generic code libraries, specialized algorithms, and formal logic. Ideally, the programming language best suited for the task at hand will be selected. Various visual programming languages have also been developed with the intent to resolve readability concerns by adopting non-traditional approaches to code structure and display.