

Text editors were also developed that allowed changes and corrections to be made much more easily than with punched cards. It is usually easier to code in "high-level" languages than in "low-level" ones. Many factors, having little or nothing to do with the ability of the computer to efficiently compile and execute the code, contribute to readability. Later a control panel (plug board) added to his 1906 Type I Tabulator allowed it to be programmed for different jobs, and by the late 1940s, unit record equipment such as the IBM 602 and IBM 604, were programmed by control panels in a similar way, as were the first electronic computers. A study found that a few simple readability transformations made code shorter and drastically reduced the time to understand it. While these are sometimes considered programming, often the term software development is used for this larger overall process – with the terms programming, implementation, and coding reserved for the writing and editing of code per se. It is very difficult to determine what are the most popular modern programming languages. This can be a non-trivial task, for example as with parallel processes or some unusual software bugs. Allen Downey, in his book *How To Think Like A Computer Scientist*, writes: Many computer languages provide a mechanism to call functions provided by shared libraries. Many applications use a mix of several languages in their construction and use. After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. For example, when a bug in a compiler can make it crash when parsing some large source file, a simplification of the test case that results in only few lines from the original source file can be sufficient to reproduce the same crash. The choice of language used is subject to many considerations, such as company policy, suitability to task, availability of third-party packages, or individual preference. Whatever the approach to development may be, the final program must satisfy some fundamental properties. Normally the first step in debugging is to attempt to reproduce the problem. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. Later a control panel (plug board) added to his 1906 Type I Tabulator allowed it to be programmed for different jobs, and by the late 1940s, unit record equipment such as the IBM 602 and IBM 604, were programmed by control panels in a similar way, as were the first electronic computers. In the 1880s, Herman Hollerith invented the concept of storing data in machine-readable form. Many programmers use forms of Agile software development where the various stages of formal software development are more integrated together into short cycles that take a few weeks rather than years. High-level languages made the process of developing a program simpler and more understandable, and less bound to the underlying hardware. Auxiliary tasks accompanying and related to programming include analyzing requirements, testing, debugging (investigating and fixing problems), implementation of build systems, and management of derived artifacts, such as programs' machine code. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. This can be a non-trivial task, for example as with parallel processes or some unusual software bugs. Following a consistent programming style often helps readability.