

For example, COBOL is still strong in corporate data centers often on large mainframe computers, Fortran in engineering applications, scripting languages in Web development, and C in embedded software. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. Also, specific user environment and usage history can make it difficult to reproduce the problem. One approach popular for requirements analysis is Use Case analysis. However, Charles Babbage had already written his first program for the Analytical Engine in 1837. For this purpose, algorithms are classified into orders using so-called Big O notation, which expresses resource use, such as execution time or memory consumption, in terms of the size of an input. Normally the first step in debugging is to attempt to reproduce the problem. Languages form an approximate spectrum from "low-level" to "high-level"; "low-level" languages are typically more machine-oriented and faster to execute, whereas "high-level" languages are more abstract and easier to use but execute less quickly. One approach popular for requirements analysis is Use Case analysis. After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. As early as the 9th century, a programmable music sequencer was invented by the Persian Banu Musa brothers, who described an automated mechanical flute player in the Book of Ingenious Devices. The choice of language used is subject to many considerations, such as company policy, suitability to task, availability of third-party packages, or individual preference. Auxiliary tasks accompanying and related to programming include analyzing requirements, testing, debugging (investigating and fixing problems), implementation of build systems, and management of derived artifacts, such as programs' machine code. For example, COBOL is still strong in corporate data centers often on large mainframe computers, Fortran in engineering applications, scripting languages in Web development, and C in embedded software. It affects the aspects of quality above, including portability, usability and most importantly maintainability. Many applications use a mix of several languages in their construction and use. A similar technique used for database design is Entity-Relationship Modeling (ER Modeling). Programming languages are essential for software development. The first computer program is generally dated to 1843, when mathematician Ada Lovelace published an algorithm to calculate a sequence of Bernoulli numbers, intended to be carried out by Charles Babbage's Analytical Engine. Different programming languages support different styles of programming (called programming paradigms). Many factors, having little or nothing to do with the ability of the computer to efficiently compile and execute the code, contribute to readability. Allen Downey, in his book *How To Think Like A Computer Scientist*, writes: Many computer languages provide a mechanism to call functions provided by shared libraries. While these are sometimes considered programming, often the term software development is used for this larger overall process – with the terms programming, implementation, and coding reserved for the writing and editing of code per se. Implementation techniques include imperative languages (object-oriented or procedural), functional languages, and logic languages. For example, when a bug in a compiler can make it crash when parsing some large source file, a simplification of the test case that results in only few lines from the original source file can be sufficient to reproduce the same crash.