

Different programming languages support different styles of programming (called programming paradigms). Debugging is a very important task in the software development process since having defects in a program can have significant consequences for its users. It is usually easier to code in "high-level" languages than in "low-level" ones. Various visual programming languages have also been developed with the intent to resolve readability concerns by adopting non-traditional approaches to code structure and display. The first computer program is generally dated to 1843, when mathematician Ada Lovelace published an algorithm to calculate a sequence of Bernoulli numbers, intended to be carried out by Charles Babbage's Analytical Engine. High-level languages made the process of developing a program simpler and more understandable, and less bound to the underlying hardware. For this purpose, algorithms are classified into orders using so-called Big O notation, which expresses resource use, such as execution time or memory consumption, in terms of the size of an input. Sometimes software development is known as software engineering, especially when it employs formal methods or follows an engineering design process. Sometimes software development is known as software engineering, especially when it employs formal methods or follows an engineering design process. For example, when a bug in a compiler can make it crash when parsing some large source file, a simplification of the test case that results in only few lines from the original source file can be sufficient to reproduce the same crash. Assembly languages were soon developed that let the programmer specify instruction in a text format (e.g., ADD X, TOTAL), with abbreviations for each operation code and meaningful names for specifying addresses. Text editors were also developed that allowed changes and corrections to be made much more easily than with punched cards. Machine code was the language of early programs, written in the instruction set of the particular machine, often in binary notation. Code-breaking algorithms have also existed for centuries. One approach popular for requirements analysis is Use Case analysis. Use of a static code analysis tool can help detect some possible problems. It is very difficult to determine what are the most popular modern programming languages. Trade-offs from this ideal involve finding enough programmers who know the language to build a team, the availability of compilers for that language, and the efficiency with which programs written in a given language execute. Trial-and-error/divide-and-conquer is needed: the programmer will try to remove some parts of the original test case and check if the problem still exists. A similar technique used for database design is Entity-Relationship Modeling (ER Modeling). In the 9th century, the Arab mathematician Al-Kindi described a cryptographic algorithm for deciphering encrypted code, in A Manuscript on Deciphering Cryptographic Messages. There are many approaches to the Software development process. Some languages are very popular for particular kinds of applications, while some languages are regularly used to write many different kinds of applications. Techniques like Code refactoring can enhance readability.