

Ideally, the programming language best suited for the task at hand will be selected. Code-breaking algorithms have also existed for centuries. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. For example, COBOL is still strong in corporate data centers often on large mainframe computers, Fortran in engineering applications, scripting languages in Web development, and C in embedded software. A study found that a few simple readability transformations made code shorter and drastically reduced the time to understand it. Many factors, having little or nothing to do with the ability of the computer to efficiently compile and execute the code, contribute to readability. Implementation techniques include imperative languages (object-oriented or procedural), functional languages, and logic languages. In the 1880s, Herman Hollerith invented the concept of storing data in machine-readable form. Programming languages are essential for software development. Implementation techniques include imperative languages (object-oriented or procedural), functional languages, and logic languages. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. Debugging is a very important task in the software development process since having defects in a program can have significant consequences for its users. In 1801, the Jacquard loom could produce entirely different weaves by changing the "program" – a series of pasteboard cards with holes punched in them. A similar technique used for database design is Entity-Relationship Modeling (ER Modeling). Programmers typically use high-level programming languages that are more easily intelligible to humans than machine code, which is directly executed by the central processing unit. Programming languages are essential for software development. Debugging is a very important task in the software development process since having defects in a program can have significant consequences for its users. Different programming languages support different styles of programming (called programming paradigms). New languages are generally designed around the syntax of a prior language with new functionality added, (for example C++ adds object-orientation to C, and Java adds memory management and bytecode to C++, but as a result, loses efficiency and the ability for low-level manipulation). Debugging is a very important task in the software development process since having defects in a program can have significant consequences for its users. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. Code-breaking algorithms have also existed for centuries. Many factors, having little or nothing to do with the ability of the computer to efficiently compile and execute the code, contribute to readability. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. Whatever the approach to development may be, the final program must satisfy some fundamental properties.