

By the late 1960s, data storage devices and computer terminals became inexpensive enough that programs could be created by typing directly into the computers. One approach popular for requirements analysis is Use Case analysis. Debugging is a very important task in the software development process since having defects in a program can have significant consequences for its users. New languages are generally designed around the syntax of a prior language with new functionality added, (for example C++ adds object-orientation to C, and Java adds memory management and bytecode to C++, but as a result, loses efficiency and the ability for low-level manipulation). It involves designing and implementing algorithms, step-by-step specifications of procedures, by writing code in one or more programming languages. Programs were mostly entered using punched cards or paper tape. Proficient programming usually requires expertise in several different subjects, including knowledge of the application domain, details of programming languages and generic code libraries, specialized algorithms, and formal logic. He gave the first description of cryptanalysis by frequency analysis, the earliest code-breaking algorithm. Debugging is often done with IDEs. Standalone debuggers like GDB are also used, and these often provide less of a visual environment, usually using a command line. Many programmers use forms of Agile software development where the various stages of formal software development are more integrated together into short cycles that take a few weeks rather than years. Integrated development environments (IDEs) aim to integrate all such help. For this purpose, algorithms are classified into orders using so-called Big O notation, which expresses resource use, such as execution time or memory consumption, in terms of the size of an input. Debugging is often done with IDEs. Standalone debuggers like GDB are also used, and these often provide less of a visual environment, usually using a command line. However, readability is more than just programming style. Programs were mostly entered using punched cards or paper tape. It affects the aspects of quality above, including portability, usability and most importantly maintainability. After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. Later a control panel (plug board) added to his 1906 Type I Tabulator allowed it to be programmed for different jobs, and by the late 1940s, unit record equipment such as the IBM 602 and IBM 604, were programmed by control panels in a similar way, as were the first electronic computers. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. Popular modeling techniques include Object-Oriented Analysis and Design (OOAD) and Model-Driven Architecture (MDA). High-level languages made the process of developing a program simpler and more understandable, and less bound to the underlying hardware. In 1801, the Jacquard loom could produce entirely different weaves by changing the "program" – a series of pasteboard cards with holes punched in them. Normally the first step in debugging is to attempt to reproduce the problem. Programs were mostly entered using punched cards or paper tape.