

However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. Computer programmers are those who write computer software. For example, COBOL is still strong in corporate data centers often on large mainframe computers, Fortran in engineering applications, scripting languages in Web development, and C in embedded software. Use of a static code analysis tool can help detect some possible problems. Normally the first step in debugging is to attempt to reproduce the problem. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. Programmers typically use high-level programming languages that are more easily intelligible to humans than machine code, which is directly executed by the central processing unit. Normally the first step in debugging is to attempt to reproduce the problem. It is very difficult to determine what are the most popular modern programming languages. For this purpose, algorithms are classified into orders using so-called Big O notation, which expresses resource use, such as execution time or memory consumption, in terms of the size of an input. Debugging is a very important task in the software development process since having defects in a program can have significant consequences for its users. Whatever the approach to development may be, the final program must satisfy some fundamental properties. Many applications use a mix of several languages in their construction and use. Trade-offs from this ideal involve finding enough programmers who know the language to build a team, the availability of compilers for that language, and the efficiency with which programs written in a given language execute. Techniques like Code refactoring can enhance readability. A study found that a few simple readability transformations made code shorter and drastically reduced the time to understand it. A similar technique used for database design is Entity-Relationship Modeling (ER Modeling). Many programmers use forms of Agile software development where the various stages of formal software development are more integrated together into short cycles that take a few weeks rather than years. The choice of language used is subject to many considerations, such as company policy, suitability to task, availability of third-party packages, or individual preference. The first step in most formal software development processes is requirements analysis, followed by testing to determine value modeling, implementation, and failure elimination (debugging). Languages form an approximate spectrum from "low-level" to "high-level"; "low-level" languages are typically more machine-oriented and faster to execute, whereas "high-level" languages are more abstract and easier to use but execute less quickly. High-level languages made the process of developing a program simpler and more understandable, and less bound to the underlying hardware. The academic field and the engineering practice of computer programming are both largely concerned with discovering and implementing the most efficient algorithms for a given class of problems. It is very difficult to determine what are the most popular modern programming languages. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research.