

Different programming languages support different styles of programming (called programming paradigms). However, with the concept of the stored-program computer introduced in 1949, both programs and data were stored and manipulated in the same way in computer memory. Assembly languages were soon developed that let the programmer specify instruction in a text format (e.g., ADD X, TOTAL), with abbreviations for each operation code and meaningful names for specifying addresses. Some of these factors include: The presentation aspects of this (such as indents, line breaks, color highlighting, and so on) are often handled by the source code editor, but the content aspects reflect the programmer's talent and skills. Some text editors such as Emacs allow GDB to be invoked through them, to provide a visual environment. This can be a non-trivial task, for example as with parallel processes or some unusual software bugs. Use of a static code analysis tool can help detect some possible problems. Many programmers use forms of Agile software development where the various stages of formal software development are more integrated together into short cycles that take a few weeks rather than years. Compilers harnessed the power of computers to make programming easier by allowing programmers to specify calculations by entering a formula using infix notation. While these are sometimes considered programming, often the term software development is used for this larger overall process – with the terms programming, implementation, and coding reserved for the writing and editing of code per se. Normally the first step in debugging is to attempt to reproduce the problem. By the late 1960s, data storage devices and computer terminals became inexpensive enough that programs could be created by typing directly into the computers. There are many approaches to the Software development process. However, with the concept of the stored-program computer introduced in 1949, both programs and data were stored and manipulated in the same way in computer memory. Implementation techniques include imperative languages (object-oriented or procedural), functional languages, and logic languages. Programmers typically use high-level programming languages that are more easily intelligible to humans than machine code, which is directly executed by the central processing unit. Techniques like Code refactoring can enhance readability. This can be a non-trivial task, for example as with parallel processes or some unusual software bugs. Computer programming or coding is the composition of sequences of instructions, called programs, that computers can follow to perform tasks. Trade-offs from this ideal involve finding enough programmers who know the language to build a team, the availability of compilers for that language, and the efficiency with which programs written in a given language execute. While these are sometimes considered programming, often the term software development is used for this larger overall process – with the terms programming, implementation, and coding reserved for the writing and editing of code per se. Assembly languages were soon developed that let the programmer specify instruction in a text format (e.g., ADD X, TOTAL), with abbreviations for each operation code and meaningful names for specifying addresses. Assembly languages were soon developed that let the programmer specify instruction in a text format (e.g., ADD X, TOTAL), with abbreviations for each operation code and meaningful names for specifying addresses. Normally the first step in debugging is to attempt to reproduce the problem. There are many approaches to the Software development process.