

Expert programmers are familiar with a variety of well-established algorithms and their respective complexities and use this knowledge to choose algorithms that are best suited to the circumstances. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. Different programming languages support different styles of programming (called programming paradigms). Provided the functions in a library follow the appropriate run-time conventions (e.g., method of passing arguments), then these functions may be written in any other language. The academic field and the engineering practice of computer programming are both largely concerned with discovering and implementing the most efficient algorithms for a given class of problems. Code-breaking algorithms have also existed for centuries. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. It is very difficult to determine what are the most popular modern programming languages. Sometimes software development is known as software engineering, especially when it employs formal methods or follows an engineering design process. High-level languages made the process of developing a program simpler and more understandable, and less bound to the underlying hardware. By the late 1960s, data storage devices and computer terminals became inexpensive enough that programs could be created by typing directly into the computers. Programmable devices have existed for centuries. It is usually easier to code in "high-level" languages than in "low-level" ones. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. Some of these factors include: The presentation aspects of this (such as indents, line breaks, color highlighting, and so on) are often handled by the source code editor, but the content aspects reflect the programmer's talent and skills. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. Computer programmers are those who write computer software. Auxiliary tasks accompanying and related to programming include analyzing requirements, testing, debugging (investigating and fixing problems), implementation of build systems, and management of derived artifacts, such as programs' machine code. Integrated development environments (IDEs) aim to integrate all such help. For example, when a bug in a compiler can make it crash when parsing some large source file, a simplification of the test case that results in only few lines from the original source file can be sufficient to reproduce the same crash. Sometimes software development is known as software engineering, especially when it employs formal methods or follows an engineering design process. Their jobs usually involve: Although programming has been presented in the media as a somewhat mathematical subject, some research shows that good programmers have strong skills in natural human languages, and that learning to code is similar to learning a foreign language.