

Auxiliary tasks accompanying and related to programming include analyzing requirements, testing, debugging (investigating and fixing problems), implementation of build systems, and management of derived artifacts, such as programs' machine code. For this purpose, algorithms are classified into orders using so-called Big O notation, which expresses resource use, such as execution time or memory consumption, in terms of the size of an input. It is usually easier to code in "high-level" languages than in "low-level" ones. Computer programmers are those who write computer software. For example, COBOL is still strong in corporate data centers often on large mainframe computers, Fortran in engineering applications, scripting languages in Web development, and C in embedded software. Sometimes software development is known as software engineering, especially when it employs formal methods or follows an engineering design process. Ideally, the programming language best suited for the task at hand will be selected. Different programming languages support different styles of programming (called programming paradigms). Different programming languages support different styles of programming (called programming paradigms). Techniques like Code refactoring can enhance readability. After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. Some of these factors include: The presentation aspects of this (such as indents, line breaks, color highlighting, and so on) are often handled by the source code editor, but the content aspects reflect the programmer's talent and skills. In the 9th century, the Arab mathematician Al-Kindi described a cryptographic algorithm for deciphering encrypted code, in A Manuscript on Deciphering Cryptographic Messages. Various visual programming languages have also been developed with the intent to resolve readability concerns by adopting non-traditional approaches to code structure and display. However, with the concept of the stored-program computer introduced in 1949, both programs and data were stored and manipulated in the same way in computer memory. Many programmers use forms of Agile software development where the various stages of formal software development are more integrated together into short cycles that take a few weeks rather than years. Popular modeling techniques include Object-Oriented Analysis and Design (OOAD) and Model-Driven Architecture (MDA). The academic field and the engineering practice of computer programming are both largely concerned with discovering and implementing the most efficient algorithms for a given class of problems. A study found that a few simple readability transformations made code shorter and drastically reduced the time to understand it. Scripting and breakpointing is also part of this process. It is usually easier to code in "high-level" languages than in "low-level" ones. After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. Unreadable code often leads to bugs, inefficiencies, and duplicated code. Following a consistent programming style often helps readability.