

Programmable devices have existed for centuries. Provided the functions in a library follow the appropriate run-time conventions (e.g., method of passing arguments), then these functions may be written in any other language. It involves designing and implementing algorithms, step-by-step specifications of procedures, by writing code in one or more programming languages. Assembly languages were soon developed that let the programmer specify instruction in a text format (e.g., ADD X, TOTAL), with abbreviations for each operation code and meaningful names for specifying addresses. Unreadable code often leads to bugs, inefficiencies, and duplicated code. Normally the first step in debugging is to attempt to reproduce the problem. High-level languages made the process of developing a program simpler and more understandable, and less bound to the underlying hardware. Debugging is often done with IDEs. Standalone debuggers like GDB are also used, and these often provide less of a visual environment, usually using a command line. Many factors, having little or nothing to do with the ability of the computer to efficiently compile and execute the code, contribute to readability. There are many approaches to the Software development process. Computer programmers are those who write computer software. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. Some of these factors include: The presentation aspects of this (such as indents, line breaks, color highlighting, and so on) are often handled by the source code editor, but the content aspects reflect the programmer's talent and skills. It involves designing and implementing algorithms, step-by-step specifications of procedures, by writing code in one or more programming languages. This can be a non-trivial task, for example as with parallel processes or some unusual software bugs. In 1206, the Arab engineer Al-Jazari invented a programmable drum machine where a musical mechanical automaton could be made to play different rhythms and drum patterns, via pegs and cams. In 1801, the Jacquard loom could produce entirely different weaves by changing the "program" – a series of pasteboard cards with holes punched in them. It is very difficult to determine what are the most popular modern programming languages. However, readability is more than just programming style. For example, COBOL is still strong in corporate data centers often on large mainframe computers, Fortran in engineering applications, scripting languages in Web development, and C in embedded software. Some languages are very popular for particular kinds of applications, while some languages are regularly used to write many different kinds of applications. Ideally, the programming language best suited for the task at hand will be selected. This can be a non-trivial task, for example as with parallel processes or some unusual software bugs. Later a control panel (plug board) added to his 1906 Type I Tabulator allowed it to be programmed for different jobs, and by the late 1940s, unit record equipment such as the IBM 602 and IBM 604, were programmed by control panels in a similar way, as were the first electronic computers. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages.