

Normally the first step in debugging is to attempt to reproduce the problem. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. For this purpose, algorithms are classified into orders using so-called Big O notation, which expresses resource use, such as execution time or memory consumption, in terms of the size of an input. Code-breaking algorithms have also existed for centuries. Methods of measuring programming language popularity include: counting the number of job advertisements that mention the language, the number of books sold and courses teaching the language (this overestimates the importance of newer languages), and estimates of the number of existing lines of code written in the language (this underestimates the number of users of business languages such as COBOL). Machine code was the language of early programs, written in the instruction set of the particular machine, often in binary notation. The choice of language used is subject to many considerations, such as company policy, suitability to task, availability of third-party packages, or individual preference. There exist a lot of different approaches for each of those tasks. In the 9th century, the Arab mathematician Al-Kindi described a cryptographic algorithm for deciphering encrypted code, in A Manuscript on Deciphering Cryptographic Messages. The choice of language used is subject to many considerations, such as company policy, suitability to task, availability of third-party packages, or individual preference. Assembly languages were soon developed that let the programmer specify instruction in a text format (e.g., ADD X, TOTAL), with abbreviations for each operation code and meaningful names for specifying addresses. Debugging is a very important task in the software development process since having defects in a program can have significant consequences for its users. Programming languages are essential for software development. Their jobs usually involve: Although programming has been presented in the media as a somewhat mathematical subject, some research shows that good programmers have strong skills in natural human languages, and that learning to code is similar to learning a foreign language. It is usually easier to code in "high-level" languages than in "low-level" ones. While these are sometimes considered programming, often the term software development is used for this larger overall process – with the terms programming, implementation, and coding reserved for the writing and editing of code per se. The first step in most formal software development processes is requirements analysis, followed by testing to determine value modeling, implementation, and failure elimination (debugging). Languages form an approximate spectrum from "low-level" to "high-level"; "low-level" languages are typically more machine-oriented and faster to execute, whereas "high-level" languages are more abstract and easier to use but execute less quickly. However, readability is more than just programming style. He gave the first description of cryptanalysis by frequency analysis, the earliest code-breaking algorithm. Computer programming or coding is the composition of sequences of instructions, called programs, that computers can follow to perform tasks. By the late 1960s, data storage devices and computer terminals became inexpensive enough that programs could be created by typing directly into the computers. A study found that a few simple readability transformations made code shorter and drastically reduced the time to understand it. After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug.