

Programming languages are essential for software development. Readability is important because programmers spend the majority of their time reading, trying to understand, reusing and modifying existing source code, rather than writing new source code. It is very difficult to determine what are the most popular modern programming languages. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. Assembly languages were soon developed that let the programmer specify instruction in a text format (e.g., ADD X, TOTAL), with abbreviations for each operation code and meaningful names for specifying addresses. It affects the aspects of quality above, including portability, usability and most importantly maintainability. Also, specific user environment and usage history can make it difficult to reproduce the problem. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. Many programmers use forms of Agile software development where the various stages of formal software development are more integrated together into short cycles that take a few weeks rather than years. Whatever the approach to development may be, the final program must satisfy some fundamental properties. Allen Downey, in his book *How To Think Like A Computer Scientist*, writes: Many computer languages provide a mechanism to call functions provided by shared libraries. Languages form an approximate spectrum from "low-level" to "high-level"; "low-level" languages are typically more machine-oriented and faster to execute, whereas "high-level" languages are more abstract and easier to use but execute less quickly. For this purpose, algorithms are classified into orders using so-called Big O notation, which expresses resource use, such as execution time or memory consumption, in terms of the size of an input. Computer programming or coding is the composition of sequences of instructions, called programs, that computers can follow to perform tasks. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. Some languages are very popular for particular kinds of applications, while some languages are regularly used to write many different kinds of applications. Many programmers use forms of Agile software development where the various stages of formal software development are more integrated together into short cycles that take a few weeks rather than years. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. The first step in most formal software development processes is requirements analysis, followed by testing to determine value modeling, implementation, and failure elimination (debugging). Many factors, having little or nothing to do with the ability of the computer to efficiently compile and execute the code, contribute to readability. These compiled languages allow the programmer to write programs in terms that are syntactically richer, and more capable of abstracting the code, making it easy to target varying machine instruction sets via compilation declarations and heuristics. Trial-and-error/divide-and-conquer is needed: the programmer will try to remove some parts of the original test case and check if the problem still exists. There are many approaches to the Software development process. A study found that a few simple readability transformations made code shorter and drastically reduced the time to understand it. Following a consistent programming style often helps readability.