

This can be a non-trivial task, for example as with parallel processes or some unusual software bugs. Debugging is a very important task in the software development process since having defects in a program can have significant consequences for its users. However, readability is more than just programming style. It is very difficult to determine what are the most popular modern programming languages. However, with the concept of the stored-program computer introduced in 1949, both programs and data were stored and manipulated in the same way in computer memory. They are the building blocks for all software, from the simplest applications to the most sophisticated ones. Later a control panel (plug board) added to his 1906 Type I Tabulator allowed it to be programmed for different jobs, and by the late 1940s, unit record equipment such as the IBM 602 and IBM 604, were programmed by control panels in a similar way, as were the first electronic computers. It is usually easier to code in "high-level" languages than in "low-level" ones. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. Unreadable code often leads to bugs, inefficiencies, and duplicated code. Expert programmers are familiar with a variety of well-established algorithms and their respective complexities and use this knowledge to choose algorithms that are best suited to the circumstances. After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. Programmers typically use high-level programming languages that are more easily intelligible to humans than machine code, which is directly executed by the central processing unit. One approach popular for requirements analysis is Use Case analysis. Their jobs usually involve: Although programming has been presented in the media as a somewhat mathematical subject, some research shows that good programmers have strong skills in natural human languages, and that learning to code is similar to learning a foreign language. New languages are generally designed around the syntax of a prior language with new functionality added, (for example C++ adds object-orientation to C, and Java adds memory management and bytecode to C++, but as a result, loses efficiency and the ability for low-level manipulation). For example, COBOL is still strong in corporate data centers often on large mainframe computers, Fortran in engineering applications, scripting languages in Web development, and C in embedded software. The first step in most formal software development processes is requirements analysis, followed by testing to determine value modeling, implementation, and failure elimination (debugging). The academic field and the engineering practice of computer programming are both largely concerned with discovering and implementing the most efficient algorithms for a given class of problems. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. As early as the 9th century, a programmable music sequencer was invented by the Persian Banu Musa brothers, who described an automated mechanical flute player in the Book of Ingenious Devices. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. Following a consistent programming style often helps readability. A similar technique used for database design is Entity-Relationship Modeling (ER Modeling). There are many approaches to the Software development process.