

After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. A study found that a few simple readability transformations made code shorter and drastically reduced the time to understand it. He gave the first description of cryptanalysis by frequency analysis, the earliest code-breaking algorithm. A similar technique used for database design is Entity-Relationship Modeling (ER Modeling). Many factors, having little or nothing to do with the ability of the computer to efficiently compile and execute the code, contribute to readability. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. Later a control panel (plug board) added to his 1906 Type I Tabulator allowed it to be programmed for different jobs, and by the late 1940s, unit record equipment such as the IBM 602 and IBM 604, were programmed by control panels in a similar way, as were the first electronic computers. Programming languages are essential for software development. Ideally, the programming language best suited for the task at hand will be selected. Some of these factors include: The presentation aspects of this (such as indents, line breaks, color highlighting, and so on) are often handled by the source code editor, but the content aspects reflect the programmer's talent and skills. Some text editors such as Emacs allow GDB to be invoked through them, to provide a visual environment. He gave the first description of cryptanalysis by frequency analysis, the earliest code-breaking algorithm. For example, when a bug in a compiler can make it crash when parsing some large source file, a simplification of the test case that results in only few lines from the original source file can be sufficient to reproduce the same crash. Methods of measuring programming language popularity include: counting the number of job advertisements that mention the language, the number of books sold and courses teaching the language (this overestimates the importance of newer languages), and estimates of the number of existing lines of code written in the language (this underestimates the number of users of business languages such as COBOL). As early as the 9th century, a programmable music sequencer was invented by the Persian Banu Musa brothers, who described an automated mechanical flute player in the Book of Ingenious Devices. Debugging is a very important task in the software development process since having defects in a program can have significant consequences for its users. Programming languages are essential for software development. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. Implementation techniques include imperative languages (object-oriented or procedural), functional languages, and logic languages. The academic field and the engineering practice of computer programming are both largely concerned with discovering and implementing the most efficient algorithms for a given class of problems. When debugging the problem in a GUI, the programmer can try to skip some user interaction from the original problem description and check if remaining actions are sufficient for bugs to appear. New languages are generally designed around the syntax of a prior language with new functionality added, (for example C++ adds object-orientation to C, and Java adds memory management and bytecode to C++, but as a result, loses efficiency and the ability for low-level manipulation). When debugging the problem in a GUI, the programmer can try to skip some user interaction from the original problem description and check if remaining actions are sufficient for bugs to appear. Code-breaking algorithms have also existed for centuries.