

The following properties are among the most important: In computer programming, readability refers to the ease with which a human reader can comprehend the purpose, control flow, and operation of source code. Compilers harnessed the power of computers to make programming easier by allowing programmers to specify calculations by entering a formula using infix notation. A study found that a few simple readability transformations made code shorter and drastically reduced the time to understand it. It is usually easier to code in "high-level" languages than in "low-level" ones. This can be a non-trivial task, for example as with parallel processes or some unusual software bugs. In the 1880s, Herman Hollerith invented the concept of storing data in machine-readable form. Some languages are very popular for particular kinds of applications, while some languages are regularly used to write many different kinds of applications. One approach popular for requirements analysis is Use Case analysis. They are the building blocks for all software, from the simplest applications to the most sophisticated ones. These compiled languages allow the programmer to write programs in terms that are syntactically richer, and more capable of abstracting the code, making it easy to target varying machine instruction sets via compilation declarations and heuristics. Assembly languages were soon developed that let the programmer specify instruction in a text format (e.g., ADD X, TOTAL), with abbreviations for each operation code and meaningful names for specifying addresses. Ideally, the programming language best suited for the task at hand will be selected. New languages are generally designed around the syntax of a prior language with new functionality added, (for example C++ adds object-orientation to C, and Java adds memory management and bytecode to C++, but as a result, loses efficiency and the ability for low-level manipulation). Normally the first step in debugging is to attempt to reproduce the problem. In 1801, the Jacquard loom could produce entirely different weaves by changing the "program" – a series of pasteboard cards with holes punched in them. Unreadable code often leads to bugs, inefficiencies, and duplicated code. Allen Downey, in his book *How To Think Like A Computer Scientist*, writes: Many computer languages provide a mechanism to call functions provided by shared libraries. Provided the functions in a library follow the appropriate run-time conventions (e.g., method of passing arguments), then these functions may be written in any other language. Some of these factors include: The presentation aspects of this (such as indents, line breaks, color highlighting, and so on) are often handled by the source code editor, but the content aspects reflect the programmer's talent and skills. Programs were mostly entered using punched cards or paper tape. There are many approaches to the Software development process. Ideally, the programming language best suited for the task at hand will be selected. The academic field and the engineering practice of computer programming are both largely concerned with discovering and implementing the most efficient algorithms for a given class of problems. Whatever the approach to development may be, the final program must satisfy some fundamental properties.