

The following properties are among the most important: In computer programming, readability refers to the ease with which a human reader can comprehend the purpose, control flow, and operation of source code. In the 9th century, the Arab mathematician Al-Kindi described a cryptographic algorithm for deciphering encrypted code, in *A Manuscript on Deciphering Cryptographic Messages*. It is very difficult to determine what are the most popular modern programming languages. Programmers typically use high-level programming languages that are more easily intelligible to humans than machine code, which is directly executed by the central processing unit. It affects the aspects of quality above, including portability, usability and most importantly maintainability. The academic field and the engineering practice of computer programming are both largely concerned with discovering and implementing the most efficient algorithms for a given class of problems. Some text editors such as Emacs allow GDB to be invoked through them, to provide a visual environment. After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. Various visual programming languages have also been developed with the intent to resolve readability concerns by adopting non-traditional approaches to code structure and display. Many applications use a mix of several languages in their construction and use. Ideally, the programming language best suited for the task at hand will be selected. Use of a static code analysis tool can help detect some possible problems. Trial-and-error/divide-and-conquer is needed: the programmer will try to remove some parts of the original test case and check if the problem still exists. Programming languages are essential for software development. Whatever the approach to development may be, the final program must satisfy some fundamental properties. Readability is important because programmers spend the majority of their time reading, trying to understand, reusing and modifying existing source code, rather than writing new source code. Compilers harnessed the power of computers to make programming easier by allowing programmers to specify calculations by entering a formula using infix notation. Some text editors such as Emacs allow GDB to be invoked through them, to provide a visual environment. Ideally, the programming language best suited for the task at hand will be selected. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. Text editors were also developed that allowed changes and corrections to be made much more easily than with punched cards. Provided the functions in a library follow the appropriate run-time conventions (e.g., method of passing arguments), then these functions may be written in any other language. Whatever the approach to development may be, the final program must satisfy some fundamental properties. For this purpose, algorithms are classified into orders using so-called Big O notation, which expresses resource use, such as execution time or memory consumption, in terms of the size of an input. Code-breaking algorithms have also existed for centuries.