

In 1206, the Arab engineer Al-Jazari invented a programmable drum machine where a musical mechanical automaton could be made to play different rhythms and drum patterns, via pegs and cams. Ideally, the programming language best suited for the task at hand will be selected. However, with the concept of the stored-program computer introduced in 1949, both programs and data were stored and manipulated in the same way in computer memory. This can be a non-trivial task, for example as with parallel processes or some unusual software bugs. Implementation techniques include imperative languages (object-oriented or procedural), functional languages, and logic languages. By the late 1960s, data storage devices and computer terminals became inexpensive enough that programs could be created by typing directly into the computers. The academic field and the engineering practice of computer programming are both largely concerned with discovering and implementing the most efficient algorithms for a given class of problems. One approach popular for requirements analysis is Use Case analysis. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. In the 1880s, Herman Hollerith invented the concept of storing data in machine-readable form. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. There exist a lot of different approaches for each of those tasks. Integrated development environments (IDEs) aim to integrate all such help. In 1206, the Arab engineer Al-Jazari invented a programmable drum machine where a musical mechanical automaton could be made to play different rhythms and drum patterns, via pegs and cams. For this purpose, algorithms are classified into orders using so-called Big O notation, which expresses resource use, such as execution time or memory consumption, in terms of the size of an input. The choice of language used is subject to many considerations, such as company policy, suitability to task, availability of third-party packages, or individual preference. There are many approaches to the Software development process. Some of these factors include: The presentation aspects of this (such as indents, line breaks, color highlighting, and so on) are often handled by the source code editor, but the content aspects reflect the programmer's talent and skills. Auxiliary tasks accompanying and related to programming include analyzing requirements, testing, debugging (investigating and fixing problems), implementation of build systems, and management of derived artifacts, such as programs' machine code. Normally the first step in debugging is to attempt to reproduce the problem. For example, when a bug in a compiler can make it crash when parsing some large source file, a simplification of the test case that results in only few lines from the original source file can be sufficient to reproduce the same crash. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. These compiled languages allow the programmer to write programs in terms that are syntactically richer, and more capable of abstracting the code, making it easy to target varying machine instruction sets via compilation declarations and heuristics. Use of a static code analysis tool can help detect some possible problems.