

Different programming languages support different styles of programming (called programming paradigms). Use of a static code analysis tool can help detect some possible problems. Auxiliary tasks accompanying and related to programming include analyzing requirements, testing, debugging (investigating and fixing problems), implementation of build systems, and management of derived artifacts, such as programs' machine code. Implementation techniques include imperative languages (object-oriented or procedural), functional languages, and logic languages. In 1801, the Jacquard loom could produce entirely different weaves by changing the "program" – a series of pasteboard cards with holes punched in them. Many applications use a mix of several languages in their construction and use. Compilers harnessed the power of computers to make programming easier by allowing programmers to specify calculations by entering a formula using infix notation. Code-breaking algorithms have also existed for centuries. Assembly languages were soon developed that let the programmer specify instruction in a text format (e.g., ADD X, TOTAL), with abbreviations for each operation code and meaningful names for specifying addresses. In the 1880s, Herman Hollerith invented the concept of storing data in machine-readable form. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. Assembly languages were soon developed that let the programmer specify instruction in a text format (e.g., ADD X, TOTAL), with abbreviations for each operation code and meaningful names for specifying addresses. The first computer program is generally dated to 1843, when mathematician Ada Lovelace published an algorithm to calculate a sequence of Bernoulli numbers, intended to be carried out by Charles Babbage's Analytical Engine. Different programming languages support different styles of programming (called programming paradigms). Their jobs usually involve: Although programming has been presented in the media as a somewhat mathematical subject, some research shows that good programmers have strong skills in natural human languages, and that learning to code is similar to learning a foreign language. In the 1880s, Herman Hollerith invented the concept of storing data in machine-readable form. A study found that a few simple readability transformations made code shorter and drastically reduced the time to understand it. After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. Programmable devices have existed for centuries. Trade-offs from this ideal involve finding enough programmers who know the language to build a team, the availability of compilers for that language, and the efficiency with which programs written in a given language execute. The first step in most formal software development processes is requirements analysis, followed by testing to determine value modeling, implementation, and failure elimination (debugging). High-level languages made the process of developing a program simpler and more understandable, and less bound to the underlying hardware. Some of these factors include: The presentation aspects of this (such as indents, line breaks, color highlighting, and so on) are often handled by the source code editor, but the content aspects reflect the programmer's talent and skills. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages.