

Languages form an approximate spectrum from "low-level" to "high-level"; "low-level" languages are typically more machine-oriented and faster to execute, whereas "high-level" languages are more abstract and easier to use but execute less quickly. Languages form an approximate spectrum from "low-level" to "high-level"; "low-level" languages are typically more machine-oriented and faster to execute, whereas "high-level" languages are more abstract and easier to use but execute less quickly. For example, when a bug in a compiler can make it crash when parsing some large source file, a simplification of the test case that results in only few lines from the original source file can be sufficient to reproduce the same crash. Debugging is a very important task in the software development process since having defects in a program can have significant consequences for its users. Unreadable code often leads to bugs, inefficiencies, and duplicated code. This can be a non-trivial task, for example as with parallel processes or some unusual software bugs. Debugging is a very important task in the software development process since having defects in a program can have significant consequences for its users. For example, when a bug in a compiler can make it crash when parsing some large source file, a simplification of the test case that results in only few lines from the original source file can be sufficient to reproduce the same crash. As early as the 9th century, a programmable music sequencer was invented by the Persian Banu Musa brothers, who described an automated mechanical flute player in the Book of Ingenious Devices. The first step in most formal software development processes is requirements analysis, followed by testing to determine value modeling, implementation, and failure elimination (debugging). Expert programmers are familiar with a variety of well-established algorithms and their respective complexities and use this knowledge to choose algorithms that are best suited to the circumstances. Machine code was the language of early programs, written in the instruction set of the particular machine, often in binary notation. Unreadable code often leads to bugs, inefficiencies, and duplicated code. Assembly languages were soon developed that let the programmer specify instruction in a text format (e.g., ADD X, TOTAL), with abbreviations for each operation code and meaningful names for specifying addresses. Machine code was the language of early programs, written in the instruction set of the particular machine, often in binary notation. Implementation techniques include imperative languages (object-oriented or procedural), functional languages, and logic languages. There are many approaches to the Software development process. Sometimes software development is known as software engineering, especially when it employs formal methods or follows an engineering design process. For this purpose, algorithms are classified into orders using so-called Big O notation, which expresses resource use, such as execution time or memory consumption, in terms of the size of an input. Some languages are very popular for particular kinds of applications, while some languages are regularly used to write many different kinds of applications. Debugging is often done with IDEs. Standalone debuggers like GDB are also used, and these often provide less of a visual environment, usually using a command line. After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. Debugging is a very important task in the software development process since having defects in a program can have significant consequences for its users. These compiled languages allow the programmer to write programs in terms that are syntactically richer, and more capable of abstracting the code, making it easy to target varying machine instruction sets via compilation declarations and heuristics. Many programmers use forms of Agile software development where the various stages of formal software development are more integrated together into short cycles that take a few weeks rather than years.