

Programs were mostly entered using punched cards or paper tape. High-level languages made the process of developing a program simpler and more understandable, and less bound to the underlying hardware. It is usually easier to code in "high-level" languages than in "low-level" ones. Many programmers use forms of Agile software development where the various stages of formal software development are more integrated together into short cycles that take a few weeks rather than years. Computer programmers are those who write computer software. Proficient programming usually requires expertise in several different subjects, including knowledge of the application domain, details of programming languages and generic code libraries, specialized algorithms, and formal logic. The first step in most formal software development processes is requirements analysis, followed by testing to determine value modeling, implementation, and failure elimination (debugging). Many applications use a mix of several languages in their construction and use. Trial-and-error/divide-and-conquer is needed: the programmer will try to remove some parts of the original test case and check if the problem still exists. It is usually easier to code in "high-level" languages than in "low-level" ones. Debugging is often done with IDEs. Standalone debuggers like GDB are also used, and these often provide less of a visual environment, usually using a command line. Popular modeling techniques include Object-Oriented Analysis and Design (OOAD) and Model-Driven Architecture (MDA). However, Charles Babbage had already written his first program for the Analytical Engine in 1837. However, readability is more than just programming style. Trade-offs from this ideal involve finding enough programmers who know the language to build a team, the availability of compilers for that language, and the efficiency with which programs written in a given language execute. By the late 1960s, data storage devices and computer terminals became inexpensive enough that programs could be created by typing directly into the computers. Various visual programming languages have also been developed with the intent to resolve readability concerns by adopting non-traditional approaches to code structure and display. Languages form an approximate spectrum from "low-level" to "high-level"; "low-level" languages are typically more machine-oriented and faster to execute, whereas "high-level" languages are more abstract and easier to use but execute less quickly. This can be a non-trivial task, for example as with parallel processes or some unusual software bugs. Proficient programming usually requires expertise in several different subjects, including knowledge of the application domain, details of programming languages and generic code libraries, specialized algorithms, and formal logic. There are many approaches to the Software development process. Many programmers use forms of Agile software development where the various stages of formal software development are more integrated together into short cycles that take a few weeks rather than years. It affects the aspects of quality above, including portability, usability and most importantly maintainability. Debugging is a very important task in the software development process since having defects in a program can have significant consequences for its users. It affects the aspects of quality above, including portability, usability and most importantly maintainability.