

Normally the first step in debugging is to attempt to reproduce the problem. Debugging is often done with IDEs. Standalone debuggers like GDB are also used, and these often provide less of a visual environment, usually using a command line. It affects the aspects of quality above, including portability, usability and most importantly maintainability. There exist a lot of different approaches for each of those tasks. Languages form an approximate spectrum from "low-level" to "high-level"; "low-level" languages are typically more machine-oriented and faster to execute, whereas "high-level" languages are more abstract and easier to use but execute less quickly. The first computer program is generally dated to 1843, when mathematician Ada Lovelace published an algorithm to calculate a sequence of Bernoulli numbers, intended to be carried out by Charles Babbage's Analytical Engine. A study found that a few simple readability transformations made code shorter and drastically reduced the time to understand it. Trade-offs from this ideal involve finding enough programmers who know the language to build a team, the availability of compilers for that language, and the efficiency with which programs written in a given language execute. Languages form an approximate spectrum from "low-level" to "high-level"; "low-level" languages are typically more machine-oriented and faster to execute, whereas "high-level" languages are more abstract and easier to use but execute less quickly.

Trial-and-error/divide-and-conquer is needed: the programmer will try to remove some parts of the original test case and check if the problem still exists. The following properties are among the most important: In computer programming, readability refers to the ease with which a human reader can comprehend the purpose, control flow, and operation of source code. By the late 1960s, data storage devices and computer terminals became inexpensive enough that programs could be created by typing directly into the computers. Some languages are very popular for particular kinds of applications, while some languages are regularly used to write many different kinds of applications. Languages form an approximate spectrum from "low-level" to "high-level"; "low-level" languages are typically more machine-oriented and faster to execute, whereas "high-level" languages are more abstract and easier to use but execute less quickly. However, readability is more than just programming style. Techniques like Code refactoring can enhance readability. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. He gave the first description of cryptanalysis by frequency analysis, the earliest code-breaking algorithm. There exist a lot of different approaches for each of those tasks. The following properties are among the most important: In computer programming, readability refers to the ease with which a human reader can comprehend the purpose, control flow, and operation of source code. As early as the 9th century, a programmable music sequencer was invented by the Persian Banu Musa brothers, who described an automated mechanical flute player in the Book of Ingenious Devices. Some languages are very popular for particular kinds of applications, while some languages are regularly used to write many different kinds of applications. Different programming languages support different styles of programming (called programming paradigms). It is very difficult to determine what are the most popular modern programming languages. One approach popular for requirements analysis is Use Case analysis.