

Languages form an approximate spectrum from "low-level" to "high-level"; "low-level" languages are typically more machine-oriented and faster to execute, whereas "high-level" languages are more abstract and easier to use but execute less quickly. Techniques like Code refactoring can enhance readability. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. Use of a static code analysis tool can help detect some possible problems. Allen Downey, in his book *How To Think Like A Computer Scientist*, writes: Many computer languages provide a mechanism to call functions provided by shared libraries. The choice of language used is subject to many considerations, such as company policy, suitability to task, availability of third-party packages, or individual preference. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. It involves designing and implementing algorithms, step-by-step specifications of procedures, by writing code in one or more programming languages. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. The first compiler related tool, the A-0 System, was developed in 1952 by Grace Hopper, who also coined the term 'compiler'. Also, specific user environment and usage history can make it difficult to reproduce the problem. Provided the functions in a library follow the appropriate run-time conventions (e.g., method of passing arguments), then these functions may be written in any other language. Normally the first step in debugging is to attempt to reproduce the problem. Computer programmers are those who write computer software. By the late 1960s, data storage devices and computer terminals became inexpensive enough that programs could be created by typing directly into the computers. Techniques like Code refactoring can enhance readability. For this purpose, algorithms are classified into orders using so-called Big O notation, which expresses resource use, such as execution time or memory consumption, in terms of the size of an input. Also, specific user environment and usage history can make it difficult to reproduce the problem. Integrated development environments (IDEs) aim to integrate all such help. For this purpose, algorithms are classified into orders using so-called Big O notation, which expresses resource use, such as execution time or memory consumption, in terms of the size of an input. However, readability is more than just programming style. Programming languages are essential for software development. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. High-level languages made the process of developing a program simpler and more understandable, and less bound to the underlying hardware.