

However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. The first computer program is generally dated to 1843, when mathematician Ada Lovelace published an algorithm to calculate a sequence of Bernoulli numbers, intended to be carried out by Charles Babbage's Analytical Engine. Various visual programming languages have also been developed with the intent to resolve readability concerns by adopting non-traditional approaches to code structure and display. After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. Different programming languages support different styles of programming (called programming paradigms). After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. The following properties are among the most important: In computer programming, readability refers to the ease with which a human reader can comprehend the purpose, control flow, and operation of source code. The following properties are among the most important: In computer programming, readability refers to the ease with which a human reader can comprehend the purpose, control flow, and operation of source code. Allen Downey, in his book *How To Think Like A Computer Scientist*, writes: Many computer languages provide a mechanism to call functions provided by shared libraries. Later a control panel (plug board) added to his 1906 Type I Tabulator allowed it to be programmed for different jobs, and by the late 1940s, unit record equipment such as the IBM 602 and IBM 604, were programmed by control panels in a similar way, as were the first electronic computers. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. The first step in most formal software development processes is requirements analysis, followed by testing to determine value modeling, implementation, and failure elimination (debugging). Machine code was the language of early programs, written in the instruction set of the particular machine, often in binary notation. Expert programmers are familiar with a variety of well-established algorithms and their respective complexities and use this knowledge to choose algorithms that are best suited to the circumstances. In 1801, the Jacquard loom could produce entirely different weaves by changing the "program" – a series of pasteboard cards with holes punched in them. Readability is important because programmers spend the majority of their time reading, trying to understand, reusing and modifying existing source code, rather than writing new source code. However, with the concept of the stored-program computer introduced in 1949, both programs and data were stored and manipulated in the same way in computer memory. Some text editors such as Emacs allow GDB to be invoked through them, to provide a visual environment. For this purpose, algorithms are classified into orders using so-called Big O notation, which expresses resource use, such as execution time or memory consumption, in terms of the size of an input. Different programming languages support different styles of programming (called programming paradigms). Programming languages are essential for software development. Many applications use a mix of several languages in their construction and use. They are the building blocks for all software, from the simplest applications to the most sophisticated ones. It is very difficult to determine what are the most popular modern programming languages. It is usually easier to code in "high-level" languages than in "low-level" ones.