

It involves designing and implementing algorithms, step-by-step specifications of procedures, by writing code in one or more programming languages. Assembly languages were soon developed that let the programmer specify instruction in a text format (e.g., ADD X, TOTAL), with abbreviations for each operation code and meaningful names for specifying addresses. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. Popular modeling techniques include Object-Oriented Analysis and Design (OOAD) and Model-Driven Architecture (MDA). Later a control panel (plug board) added to his 1906 Type I Tabulator allowed it to be programmed for different jobs, and by the late 1940s, unit record equipment such as the IBM 602 and IBM 604, were programmed by control panels in a similar way, as were the first electronic computers. Debugging is often done with IDEs. Standalone debuggers like GDB are also used, and these often provide less of a visual environment, usually using a command line. Ideally, the programming language best suited for the task at hand will be selected. Expert programmers are familiar with a variety of well-established algorithms and their respective complexities and use this knowledge to choose algorithms that are best suited to the circumstances. Their jobs usually involve: Although programming has been presented in the media as a somewhat mathematical subject, some research shows that good programmers have strong skills in natural human languages, and that learning to code is similar to learning a foreign language. In the 1880s, Herman Hollerith invented the concept of storing data in machine-readable form. Following a consistent programming style often helps readability. One approach popular for requirements analysis is Use Case analysis. Sometimes software development is known as software engineering, especially when it employs formal methods or follows an engineering design process. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. A similar technique used for database design is Entity-Relationship Modeling (ER Modeling). Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. Programs were mostly entered using punched cards or paper tape. Techniques like Code refactoring can enhance readability. The academic field and the engineering practice of computer programming are both largely concerned with discovering and implementing the most efficient algorithms for a given class of problems. He gave the first description of cryptanalysis by frequency analysis, the earliest code-breaking algorithm. However, with the concept of the stored-program computer introduced in 1949, both programs and data were stored and manipulated in the same way in computer memory. Many programmers use forms of Agile software development where the various stages of formal software development are more integrated together into short cycles that take a few weeks rather than years. It affects the aspects of quality above, including portability, usability and most importantly maintainability. One approach popular for requirements analysis is Use Case analysis.