

Various visual programming languages have also been developed with the intent to resolve readability concerns by adopting non-traditional approaches to code structure and display. Programmers typically use high-level programming languages that are more easily intelligible to humans than machine code, which is directly executed by the central processing unit. There are many approaches to the Software development process. Allen Downey, in his book *How To Think Like A Computer Scientist*, writes: Many computer languages provide a mechanism to call functions provided by shared libraries. Implementation techniques include imperative languages (object-oriented or procedural), functional languages, and logic languages. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. Trial-and-error/divide-and-conquer is needed: the programmer will try to remove some parts of the original test case and check if the problem still exists. Trade-offs from this ideal involve finding enough programmers who know the language to build a team, the availability of compilers for that language, and the efficiency with which programs written in a given language execute. It involves designing and implementing algorithms, step-by-step specifications of procedures, by writing code in one or more programming languages. It is very difficult to determine what are the most popular modern programming languages. When debugging the problem in a GUI, the programmer can try to skip some user interaction from the original problem description and check if remaining actions are sufficient for bugs to appear. The first step in most formal software development processes is requirements analysis, followed by testing to determine value modeling, implementation, and failure elimination (debugging). High-level languages made the process of developing a program simpler and more understandable, and less bound to the underlying hardware. Many applications use a mix of several languages in their construction and use. After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. Some of these factors include: The presentation aspects of this (such as indents, line breaks, color highlighting, and so on) are often handled by the source code editor, but the content aspects reflect the programmer's talent and skills. Readability is important because programmers spend the majority of their time reading, trying to understand, reusing and modifying existing source code, rather than writing new source code. It is usually easier to code in "high-level" languages than in "low-level" ones. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. Unreadable code often leads to bugs, inefficiencies, and duplicated code. Different programming languages support different styles of programming (called programming paradigms). In 1801, the Jacquard loom could produce entirely different weaves by changing the "program" – a series of pasteboard cards with holes punched in them. The first step in most formal software development processes is requirements analysis, followed by testing to determine value modeling, implementation, and failure elimination (debugging). Many applications use a mix of several languages in their construction and use. High-level languages made the process of developing a program simpler and more understandable, and less bound to the underlying hardware.