

Some of these factors include: The presentation aspects of this (such as indents, line breaks, color highlighting, and so on) are often handled by the source code editor, but the content aspects reflect the programmer's talent and skills. The first compiler related tool, the A-0 System, was developed in 1952 by Grace Hopper, who also coined the term 'compiler'. Implementation techniques include imperative languages (object-oriented or procedural), functional languages, and logic languages. In the 9th century, the Arab mathematician Al-Kindi described a cryptographic algorithm for deciphering encrypted code, in A Manuscript on Deciphering Cryptographic Messages. Programmable devices have existed for centuries. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. As early as the 9th century, a programmable music sequencer was invented by the Persian Banu Musa brothers, who described an automated mechanical flute player in the Book of Ingenious Devices. Integrated development environments (IDEs) aim to integrate all such help. Assembly languages were soon developed that let the programmer specify instruction in a text format (e.g., ADD X, TOTAL), with abbreviations for each operation code and meaningful names for specifying addresses. Use of a static code analysis tool can help detect some possible problems. Programmable devices have existed for centuries. When debugging the problem in a GUI, the programmer can try to skip some user interaction from the original problem description and check if remaining actions are sufficient for bugs to appear. However, Charles Babbage had already written his first program for the Analytical Engine in 1837. There exist a lot of different approaches for each of those tasks. However, with the concept of the stored-program computer introduced in 1949, both programs and data were stored and manipulated in the same way in computer memory. It affects the aspects of quality above, including portability, usability and most importantly maintainability. Also, specific user environment and usage history can make it difficult to reproduce the problem. There are many approaches to the Software development process. There exist a lot of different approaches for each of those tasks. Compilers harnessed the power of computers to make programming easier by allowing programmers to specify calculations by entering a formula using infix notation. New languages are generally designed around the syntax of a prior language with new functionality added, (for example C++ adds object-orientation to C, and Java adds memory management and bytecode to C++, but as a result, loses efficiency and the ability for low-level manipulation). Popular modeling techniques include Object-Oriented Analysis and Design (OOAD) and Model-Driven Architecture (MDA). When debugging the problem in a GUI, the programmer can try to skip some user interaction from the original problem description and check if remaining actions are sufficient for bugs to appear. A study found that a few simple readability transformations made code shorter and drastically reduced the time to understand it. By the late 1960s, data storage devices and computer terminals became inexpensive enough that programs could be created by typing directly into the computers.