

Programs were mostly entered using punched cards or paper tape. Allen Downey, in his book *How To Think Like A Computer Scientist*, writes: Many computer languages provide a mechanism to call functions provided by shared libraries. Many programmers use forms of Agile software development where the various stages of formal software development are more integrated together into short cycles that take a few weeks rather than years. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. A similar technique used for database design is Entity-Relationship Modeling (ER Modeling). Many applications use a mix of several languages in their construction and use. Some languages are very popular for particular kinds of applications, while some languages are regularly used to write many different kinds of applications. Proficient programming usually requires expertise in several different subjects, including knowledge of the application domain, details of programming languages and generic code libraries, specialized algorithms, and formal logic. Scripting and breakpointing is also part of this process. Implementation techniques include imperative languages (object-oriented or procedural), functional languages, and logic languages. Some text editors such as Emacs allow GDB to be invoked through them, to provide a visual environment. For this purpose, algorithms are classified into orders using so-called Big O notation, which expresses resource use, such as execution time or memory consumption, in terms of the size of an input. Whatever the approach to development may be, the final program must satisfy some fundamental properties. Whatever the approach to development may be, the final program must satisfy some fundamental properties. Following a consistent programming style often helps readability. Integrated development environments (IDEs) aim to integrate all such help. Compilers harnessed the power of computers to make programming easier by allowing programmers to specify calculations by entering a formula using infix notation. The choice of language used is subject to many considerations, such as company policy, suitability to task, availability of third-party packages, or individual preference. Programmers typically use high-level programming languages that are more easily intelligible to humans than machine code, which is directly executed by the central processing unit. Provided the functions in a library follow the appropriate run-time conventions (e.g., method of passing arguments), then these functions may be written in any other language. Later a control panel (plug board) added to his 1906 Type I Tabulator allowed it to be programmed for different jobs, and by the late 1940s, unit record equipment such as the IBM 602 and IBM 604, were programmed by control panels in a similar way, as were the first electronic computers. Compilers harnessed the power of computers to make programming easier by allowing programmers to specify calculations by entering a formula using infix notation. Many factors, having little or nothing to do with the ability of the computer to efficiently compile and execute the code, contribute to readability. Many factors, having little or nothing to do with the ability of the computer to efficiently compile and execute the code, contribute to readability.