

The first computer program is generally dated to 1843, when mathematician Ada Lovelace published an algorithm to calculate a sequence of Bernoulli numbers, intended to be carried out by Charles Babbage's Analytical Engine. Normally the first step in debugging is to attempt to reproduce the problem. Proficient programming usually requires expertise in several different subjects, including knowledge of the application domain, details of programming languages and generic code libraries, specialized algorithms, and formal logic. High-level languages made the process of developing a program simpler and more understandable, and less bound to the underlying hardware. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. The choice of language used is subject to many considerations, such as company policy, suitability to task, availability of third-party packages, or individual preference. Debugging is often done with IDEs. Standalone debuggers like GDB are also used, and these often provide less of a visual environment, usually using a command line. Many programmers use forms of Agile software development where the various stages of formal software development are more integrated together into short cycles that take a few weeks rather than years. Programming languages are essential for software development. After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. The academic field and the engineering practice of computer programming are both largely concerned with discovering and implementing the most efficient algorithms for a given class of problems. Normally the first step in debugging is to attempt to reproduce the problem. Proficient programming usually requires expertise in several different subjects, including knowledge of the application domain, details of programming languages and generic code libraries, specialized algorithms, and formal logic. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. Some languages are very popular for particular kinds of applications, while some languages are regularly used to write many different kinds of applications. Many factors, having little or nothing to do with the ability of the computer to efficiently compile and execute the code, contribute to readability. Sometimes software development is known as software engineering, especially when it employs formal methods or follows an engineering design process. In the 9th century, the Arab mathematician Al-Kindi described a cryptographic algorithm for deciphering encrypted code, in A Manuscript on Deciphering Cryptographic Messages. While these are sometimes considered programming, often the term software development is used for this larger overall process – with the terms programming, implementation, and coding reserved for the writing and editing of code per se. For example, when a bug in a compiler can make it crash when parsing some large source file, a simplification of the test case that results in only few lines from the original source file can be sufficient to reproduce the same crash. In the 9th century, the Arab mathematician Al-Kindi described a cryptographic algorithm for deciphering encrypted code, in A Manuscript on Deciphering Cryptographic Messages. It involves designing and implementing algorithms, step-by-step specifications of procedures, by writing code in one or more programming languages. The first computer program is generally dated to 1843, when mathematician Ada Lovelace published an algorithm to calculate a sequence of Bernoulli numbers, intended to be carried out by Charles Babbage's Analytical Engine. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. Integrated development environments (IDEs) aim to integrate all such help.