

However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. This can be a non-trivial task, for example as with parallel processes or some unusual software bugs. He gave the first description of cryptanalysis by frequency analysis, the earliest code-breaking algorithm. Programmers typically use high-level programming languages that are more easily intelligible to humans than machine code, which is directly executed by the central processing unit. Provided the functions in a library follow the appropriate run-time conventions (e.g., method of passing arguments), then these functions may be written in any other language. Assembly languages were soon developed that let the programmer specify instruction in a text format (e.g., ADD X, TOTAL), with abbreviations for each operation code and meaningful names for specifying addresses. The first step in most formal software development processes is requirements analysis, followed by testing to determine value modeling, implementation, and failure elimination (debugging). In the 9th century, the Arab mathematician Al-Kindi described a cryptographic algorithm for deciphering encrypted code, in A Manuscript on Deciphering Cryptographic Messages. Following a consistent programming style often helps readability. Following a consistent programming style often helps readability. New languages are generally designed around the syntax of a prior language with new functionality added, (for example C++ adds object-orientation to C, and Java adds memory management and bytecode to C++, but as a result, loses efficiency and the ability for low-level manipulation). High-level languages made the process of developing a program simpler and more understandable, and less bound to the underlying hardware. Following a consistent programming style often helps readability. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. Normally the first step in debugging is to attempt to reproduce the problem. The first computer program is generally dated to 1843, when mathematician Ada Lovelace published an algorithm to calculate a sequence of Bernoulli numbers, intended to be carried out by Charles Babbage's Analytical Engine. Unreadable code often leads to bugs, inefficiencies, and duplicated code. While these are sometimes considered programming, often the term software development is used for this larger overall process – with the terms programming, implementation, and coding reserved for the writing and editing of code per se. High-level languages made the process of developing a program simpler and more understandable, and less bound to the underlying hardware. Later a control panel (plug board) added to his 1906 Type I Tabulator allowed it to be programmed for different jobs, and by the late 1940s, unit record equipment such as the IBM 602 and IBM 604, were programmed by control panels in a similar way, as were the first electronic computers. For example, COBOL is still strong in corporate data centers often on large mainframe computers, Fortran in engineering applications, scripting languages in Web development, and C in embedded software. The choice of language used is subject to many considerations, such as company policy, suitability to task, availability of third-party packages, or individual preference. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. For example, when a bug in a compiler can make it crash when parsing some large source file, a simplification of the test case that results in only few lines from the original source file can be sufficient to reproduce the same crash.