

The choice of language used is subject to many considerations, such as company policy, suitability to task, availability of third-party packages, or individual preference. Some of these factors include: The presentation aspects of this (such as indents, line breaks, color highlighting, and so on) are often handled by the source code editor, but the content aspects reflect the programmer's talent and skills. Many applications use a mix of several languages in their construction and use. Later a control panel (plug board) added to his 1906 Type I Tabulator allowed it to be programmed for different jobs, and by the late 1940s, unit record equipment such as the IBM 602 and IBM 604, were programmed by control panels in a similar way, as were the first electronic computers. Scripting and breakpointing is also part of this process. Many factors, having little or nothing to do with the ability of the computer to efficiently compile and execute the code, contribute to readability. By the late 1960s, data storage devices and computer terminals became inexpensive enough that programs could be created by typing directly into the computers. In the 9th century, the Arab mathematician Al-Kindi described a cryptographic algorithm for deciphering encrypted code, in A Manuscript on Deciphering Cryptographic Messages. Implementation techniques include imperative languages (object-oriented or procedural), functional languages, and logic languages. Programmers typically use high-level programming languages that are more easily intelligible to humans than machine code, which is directly executed by the central processing unit. Assembly languages were soon developed that let the programmer specify instruction in a text format (e.g., ADD X, TOTAL), with abbreviations for each operation code and meaningful names for specifying addresses. They are the building blocks for all software, from the simplest applications to the most sophisticated ones. By the late 1960s, data storage devices and computer terminals became inexpensive enough that programs could be created by typing directly into the computers. The first step in most formal software development processes is requirements analysis, followed by testing to determine value modeling, implementation, and failure elimination (debugging). In 1206, the Arab engineer Al-Jazari invented a programmable drum machine where a musical mechanical automaton could be made to play different rhythms and drum patterns, via pegs and cams. Various visual programming languages have also been developed with the intent to resolve readability concerns by adopting non-traditional approaches to code structure and display. For example, COBOL is still strong in corporate data centers often on large mainframe computers, Fortran in engineering applications, scripting languages in Web development, and C in embedded software. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. Some languages are very popular for particular kinds of applications, while some languages are regularly used to write many different kinds of applications. Also, specific user environment and usage history can make it difficult to reproduce the problem. Some languages are very popular for particular kinds of applications, while some languages are regularly used to write many different kinds of applications. Trial-and-error/divide-and-conquer is needed: the programmer will try to remove some parts of the original test case and check if the problem still exists. Compilers harnessed the power of computers to make programming easier by allowing programmers to specify calculations by entering a formula using infix notation. The academic field and the engineering practice of computer programming are both largely concerned with discovering and implementing the most efficient algorithms for a given class of problems. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages.