

It is usually easier to code in "high-level" languages than in "low-level" ones. Many applications use a mix of several languages in their construction and use. The first compiler related tool, the A-0 System, was developed in 1952 by Grace Hopper, who also coined the term 'compiler'. Assembly languages were soon developed that let the programmer specify instruction in a text format (e.g., ADD X, TOTAL), with abbreviations for each operation code and meaningful names for specifying addresses. Provided the functions in a library follow the appropriate run-time conventions (e.g., method of passing arguments), then these functions may be written in any other language. After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. Methods of measuring programming language popularity include: counting the number of job advertisements that mention the language, the number of books sold and courses teaching the language (this overestimates the importance of newer languages), and estimates of the number of existing lines of code written in the language (this underestimates the number of users of business languages such as COBOL). In the 1880s, Herman Hollerith invented the concept of storing data in machine-readable form. This can be a non-trivial task, for example as with parallel processes or some unusual software bugs. The first compiler related tool, the A-0 System, was developed in 1952 by Grace Hopper, who also coined the term 'compiler'. For example, when a bug in a compiler can make it crash when parsing some large source file, a simplification of the test case that results in only few lines from the original source file can be sufficient to reproduce the same crash. However, readability is more than just programming style. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. Ideally, the programming language best suited for the task at hand will be selected. Languages form an approximate spectrum from "low-level" to "high-level"; "low-level" languages are typically more machine-oriented and faster to execute, whereas "high-level" languages are more abstract and easier to use but execute less quickly. A similar technique used for database design is Entity-Relationship Modeling (ER Modeling). It involves designing and implementing algorithms, step-by-step specifications of procedures, by writing code in one or more programming languages. Some text editors such as Emacs allow GDB to be invoked through them, to provide a visual environment. Techniques like Code refactoring can enhance readability. The academic field and the engineering practice of computer programming are both largely concerned with discovering and implementing the most efficient algorithms for a given class of problems. He gave the first description of cryptanalysis by frequency analysis, the earliest code-breaking algorithm. It affects the aspects of quality above, including portability, usability and most importantly maintainability. In 1801, the Jacquard loom could produce entirely different weaves by changing the "program" – a series of pasteboard cards with holes punched in them. The following properties are among the most important: In computer programming, readability refers to the ease with which a human reader can comprehend the purpose, control flow, and operation of source code.