

Compilers harnessed the power of computers to make programming easier by allowing programmers to specify calculations by entering a formula using infix notation. Allen Downey, in his book *How To Think Like A Computer Scientist*, writes: Many computer languages provide a mechanism to call functions provided by shared libraries. Scripting and breakpointing is also part of this process. Text editors were also developed that allowed changes and corrections to be made much more easily than with punched cards. A study found that a few simple readability transformations made code shorter and drastically reduced the time to understand it. The first computer program is generally dated to 1843, when mathematician Ada Lovelace published an algorithm to calculate a sequence of Bernoulli numbers, intended to be carried out by Charles Babbage's Analytical Engine. For example, when a bug in a compiler can make it crash when parsing some large source file, a simplification of the test case that results in only few lines from the original source file can be sufficient to reproduce the same crash. They are the building blocks for all software, from the simplest applications to the most sophisticated ones. Programs were mostly entered using punched cards or paper tape. In 1206, the Arab engineer Al-Jazari invented a programmable drum machine where a musical mechanical automaton could be made to play different rhythms and drum patterns, via pegs and cams. Some languages are very popular for particular kinds of applications, while some languages are regularly used to write many different kinds of applications. Normally the first step in debugging is to attempt to reproduce the problem. The first computer program is generally dated to 1843, when mathematician Ada Lovelace published an algorithm to calculate a sequence of Bernoulli numbers, intended to be carried out by Charles Babbage's Analytical Engine. Many programmers use forms of Agile software development where the various stages of formal software development are more integrated together into short cycles that take a few weeks rather than years. It affects the aspects of quality above, including portability, usability and most importantly maintainability. After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. Assembly languages were soon developed that let the programmer specify instruction in a text format (e.g., ADD X, TOTAL), with abbreviations for each operation code and meaningful names for specifying addresses. For example, COBOL is still strong in corporate data centers often on large mainframe computers, Fortran in engineering applications, scripting languages in Web development, and C in embedded software. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. It involves designing and implementing algorithms, step-by-step specifications of procedures, by writing code in one or more programming languages. Implementation techniques include imperative languages (object-oriented or procedural), functional languages, and logic languages. Many applications use a mix of several languages in their construction and use.