

Assembly languages were soon developed that let the programmer specify instruction in a text format (e.g., ADD X, TOTAL), with abbreviations for each operation code and meaningful names for specifying addresses. Trade-offs from this ideal involve finding enough programmers who know the language to build a team, the availability of compilers for that language, and the efficiency with which programs written in a given language execute. Programmers typically use high-level programming languages that are more easily intelligible to humans than machine code, which is directly executed by the central processing unit. Whatever the approach to development may be, the final program must satisfy some fundamental properties. There are many approaches to the Software development process. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. Later a control panel (plug board) added to his 1906 Type I Tabulator allowed it to be programmed for different jobs, and by the late 1940s, unit record equipment such as the IBM 602 and IBM 604, were programmed by control panels in a similar way, as were the first electronic computers. Programmers typically use high-level programming languages that are more easily intelligible to humans than machine code, which is directly executed by the central processing unit. Scripting and breakpointing is also part of this process. Compilers harnessed the power of computers to make programming easier by allowing programmers to specify calculations by entering a formula using infix notation. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. It involves designing and implementing algorithms, step-by-step specifications of procedures, by writing code in one or more programming languages. Machine code was the language of early programs, written in the instruction set of the particular machine, often in binary notation. Readability is important because programmers spend the majority of their time reading, trying to understand, reusing and modifying existing source code, rather than writing new source code. Scripting and breakpointing is also part of this process. It affects the aspects of quality above, including portability, usability and most importantly maintainability. Many programmers use forms of Agile software development where the various stages of formal software development are more integrated together into short cycles that take a few weeks rather than years. Provided the functions in a library follow the appropriate run-time conventions (e.g., method of passing arguments), then these functions may be written in any other language. There are many approaches to the Software development process. Computer programmers are those who write computer software. Code-breaking algorithms have also existed for centuries. For this purpose, algorithms are classified into orders using so-called Big O notation, which expresses resource use, such as execution time or memory consumption, in terms of the size of an input. Following a consistent programming style often helps readability. Popular modeling techniques include Object-Oriented Analysis and Design (OOAD) and Model-Driven Architecture (MDA).