

As early as the 9th century, a programmable music sequencer was invented by the Persian Banu Musa brothers, who described an automated mechanical flute player in the Book of Ingenious Devices. In the 1880s, Herman Hollerith invented the concept of storing data in machine-readable form. The choice of language used is subject to many considerations, such as company policy, suitability to task, availability of third-party packages, or individual preference. Languages form an approximate spectrum from "low-level" to "high-level"; "low-level" languages are typically more machine-oriented and faster to execute, whereas "high-level" languages are more abstract and easier to use but execute less quickly. Some languages are very popular for particular kinds of applications, while some languages are regularly used to write many different kinds of applications. Normally the first step in debugging is to attempt to reproduce the problem. Implementation techniques include imperative languages (object-oriented or procedural), functional languages, and logic languages. Also, specific user environment and usage history can make it difficult to reproduce the problem. It affects the aspects of quality above, including portability, usability and most importantly maintainability. By the late 1960s, data storage devices and computer terminals became inexpensive enough that programs could be created by typing directly into the computers. Also, specific user environment and usage history can make it difficult to reproduce the problem. Debugging is a very important task in the software development process since having defects in a program can have significant consequences for its users. It involves designing and implementing algorithms, step-by-step specifications of procedures, by writing code in one or more programming languages. Programmers typically use high-level programming languages that are more easily intelligible to humans than machine code, which is directly executed by the central processing unit. After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. There exist a lot of different approaches for each of those tasks. For this purpose, algorithms are classified into orders using so-called Big O notation, which expresses resource use, such as execution time or memory consumption, in terms of the size of an input. Assembly languages were soon developed that let the programmer specify instruction in a text format (e.g., ADD X, TOTAL), with abbreviations for each operation code and meaningful names for specifying addresses. Some languages are very popular for particular kinds of applications, while some languages are regularly used to write many different kinds of applications. While these are sometimes considered programming, often the term software development is used for this larger overall process – with the terms programming, implementation, and coding reserved for the writing and editing of code per se. Popular modeling techniques include Object-Oriented Analysis and Design (OOAD) and Model-Driven Architecture (MDA). Compilers harnessed the power of computers to make programming easier by allowing programmers to specify calculations by entering a formula using infix notation. Programmable devices have existed for centuries. It is very difficult to determine what are the most popular modern programming languages.