Whatever the approach to development may be, the final program must satisfy some fundamental properties. Different programming languages support different styles of programming (called programming paradigms). Different programming languages support different styles of programming (called programming paradigms). The first compiler related tool, the A-0 System, was developed in 1952 by Grace Hopper, who also coined the term 'compiler'. The first step in most formal software development processes is requirements analysis, followed by testing to determine value modeling, implementation, and failure elimination (debugging). However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. For example, COBOL is still strong in corporate data centers often on large mainframe computers, Fortran in engineering applications, scripting languages in Web development, and C in embedded software. Programs were mostly entered using punched cards or paper tape. By the late 1960s, data storage devices and computer terminals became inexpensive enough that programs could be created by typing directly into the computers. There exist a lot of different approaches for each of those tasks. Readability is important because programmers spend the majority of their time reading, trying to understand, reusing and modifying existing source code, rather than writing new source code. It affects the aspects of quality above, including portability, usability and most importantly maintainability. Trial-and-error/divide-and-conquer is needed: the programmer will try to remove some parts of the original test case and check if the problem still exists. By the late 1960s, data storage devices and computer terminals became inexpensive enough that programs could be created by typing directly into the computers. High-level languages made the process of developing a program simpler and more understandable, and less bound to the underlying hardware. Sometimes software development is known as software engineering, especially when it employs formal methods or follows an engineering design process. Trial-and-error/divide-and-conguer is needed: the programmer will try to remove some parts of the original test case and check if the problem still exists. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. Readability is important because programmers spend the majority of their time reading, trying to understand, reusing and modifying existing source code, rather than writing new source code. Debugging is often done with IDEs. Standalone debuggers like GDB are also used, and these often provide less of a visual environment, usually using a command line. Their jobs usually involve: Although programming has been presented in the media as a somewhat mathematical subject, some research shows that good programmers have strong skills in natural human languages, and that learning to code is similar to learning a foreign language. Auxiliary tasks accompanying and related to programming include analyzing requirements, testing, debugging (investigating and fixing problems), implementation of build systems, and management of derived artifacts, such as programs' machine code. Readability is important because programmers spend the majority of their time reading, trying to understand, reusing and modifying existing source code, rather than writing new source code. They are the building blocks for all software, from the simplest applications to the most sophisticated ones.