

In the 9th century, the Arab mathematician Al-Kindi described a cryptographic algorithm for deciphering encrypted code, in A Manuscript on Deciphering Cryptographic Messages. Debugging is often done with IDEs. Standalone debuggers like GDB are also used, and these often provide less of a visual environment, usually using a command line. High-level languages made the process of developing a program simpler and more understandable, and less bound to the underlying hardware. For example, when a bug in a compiler can make it crash when parsing some large source file, a simplification of the test case that results in only few lines from the original source file can be sufficient to reproduce the same crash. Some of these factors include: The presentation aspects of this (such as indents, line breaks, color highlighting, and so on) are often handled by the source code editor, but the content aspects reflect the programmer's talent and skills. Machine code was the language of early programs, written in the instruction set of the particular machine, often in binary notation. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. As early as the 9th century, a programmable music sequencer was invented by the Persian Banu Musa brothers, who described an automated mechanical flute player in the Book of Ingenious Devices. In 1206, the Arab engineer Al-Jazari invented a programmable drum machine where a musical mechanical automaton could be made to play different rhythms and drum patterns, via pegs and cams. It involves designing and implementing algorithms, step-by-step specifications of procedures, by writing code in one or more programming languages. Some languages are very popular for particular kinds of applications, while some languages are regularly used to write many different kinds of applications. However, Charles Babbage had already written his first program for the Analytical Engine in 1837. Debugging is often done with IDEs. Standalone debuggers like GDB are also used, and these often provide less of a visual environment, usually using a command line. Many programmers use forms of Agile software development where the various stages of formal software development are more integrated together into short cycles that take a few weeks rather than years. Debugging is a very important task in the software development process since having defects in a program can have significant consequences for its users. In the 1880s, Herman Hollerith invented the concept of storing data in machine-readable form. Many factors, having little or nothing to do with the ability of the computer to efficiently compile and execute the code, contribute to readability. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. Allen Downey, in his book How To Think Like A Computer Scientist, writes: Many computer languages provide a mechanism to call functions provided by shared libraries. A similar technique used for database design is Entity-Relationship Modeling (ER Modeling). For example, COBOL is still strong in corporate data centers often on large mainframe computers, Fortran in engineering applications, scripting languages in Web development, and C in embedded software. The following properties are among the most important: In computer programming, readability refers to the ease with which a human reader can comprehend the purpose, control flow, and operation of source code. The first step in most formal software development processes is requirements analysis, followed by testing to determine value modeling, implementation, and failure elimination (debugging). In the 9th century, the Arab mathematician Al-Kindi described a cryptographic algorithm for deciphering encrypted code, in A Manuscript on Deciphering Cryptographic Messages.