

High-level languages made the process of developing a program simpler and more understandable, and less bound to the underlying hardware. Trade-offs from this ideal involve finding enough programmers who know the language to build a team, the availability of compilers for that language, and the efficiency with which programs written in a given language execute. The first compiler related tool, the A-0 System, was developed in 1952 by Grace Hopper, who also coined the term 'compiler'. Trade-offs from this ideal involve finding enough programmers who know the language to build a team, the availability of compilers for that language, and the efficiency with which programs written in a given language execute. In 1801, the Jacquard loom could produce entirely different weaves by changing the "program" – a series of pasteboard cards with holes punched in them. Debugging is often done with IDEs. Standalone debuggers like GDB are also used, and these often provide less of a visual environment, usually using a command line. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. The first computer program is generally dated to 1843, when mathematician Ada Lovelace published an algorithm to calculate a sequence of Bernoulli numbers, intended to be carried out by Charles Babbage's Analytical Engine. Use of a static code analysis tool can help detect some possible problems. Many applications use a mix of several languages in their construction and use. Various visual programming languages have also been developed with the intent to resolve readability concerns by adopting non-traditional approaches to code structure and display. In 1206, the Arab engineer Al-Jazari invented a programmable drum machine where a musical mechanical automaton could be made to play different rhythms and drum patterns, via pegs and cams. The choice of language used is subject to many considerations, such as company policy, suitability to task, availability of third-party packages, or individual preference. Readability is important because programmers spend the majority of their time reading, trying to understand, reusing and modifying existing source code, rather than writing new source code. Code-breaking algorithms have also existed for centuries. Scripting and breakpointing is also part of this process. A study found that a few simple readability transformations made code shorter and drastically reduced the time to understand it. However, Charles Babbage had already written his first program for the Analytical Engine in 1837. Debugging is a very important task in the software development process since having defects in a program can have significant consequences for its users. Sometimes software development is known as software engineering, especially when it employs formal methods or follows an engineering design process. In the 9th century, the Arab mathematician Al-Kindi described a cryptographic algorithm for deciphering encrypted code, in A Manuscript on Deciphering Cryptographic Messages. Programming languages are essential for software development. Ideally, the programming language best suited for the task at hand will be selected. Debugging is a very important task in the software development process since having defects in a program can have significant consequences for its users.