

While these are sometimes considered programming, often the term software development is used for this larger overall process – with the terms programming, implementation, and coding reserved for the writing and editing of code per se. In 1801, the Jacquard loom could produce entirely different weaves by changing the "program" – a series of pasteboard cards with holes punched in them. High-level languages made the process of developing a program simpler and more understandable, and less bound to the underlying hardware. As early as the 9th century, a programmable music sequencer was invented by the Persian Banu Musa brothers, who described an automated mechanical flute player in the Book of Ingenious Devices. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. Many programmers use forms of Agile software development where the various stages of formal software development are more integrated together into short cycles that take a few weeks rather than years. He gave the first description of cryptanalysis by frequency analysis, the earliest code-breaking algorithm. While these are sometimes considered programming, often the term software development is used for this larger overall process – with the terms programming, implementation, and coding reserved for the writing and editing of code per se. Scripting and breakpointing is also part of this process. Assembly languages were soon developed that let the programmer specify instruction in a text format (e.g., ADD X, TOTAL), with abbreviations for each operation code and meaningful names for specifying addresses. Normally the first step in debugging is to attempt to reproduce the problem. However, with the concept of the stored-program computer introduced in 1949, both programs and data were stored and manipulated in the same way in computer memory. They are the building blocks for all software, from the simplest applications to the most sophisticated ones. However, readability is more than just programming style. Many applications use a mix of several languages in their construction and use. Unreadable code often leads to bugs, inefficiencies, and duplicated code. The first step in most formal software development processes is requirements analysis, followed by testing to determine value modeling, implementation, and failure elimination (debugging). Whatever the approach to development may be, the final program must satisfy some fundamental properties. Techniques like Code refactoring can enhance readability. There are many approaches to the Software development process. In the 1880s, Herman Hollerith invented the concept of storing data in machine-readable form. Computer programmers are those who write computer software. New languages are generally designed around the syntax of a prior language with new functionality added, (for example C++ adds object-orientation to C, and Java adds memory management and bytecode to C++, but as a result, loses efficiency and the ability for low-level manipulation). It is usually easier to code in "high-level" languages than in "low-level" ones. Readability is important because programmers spend the majority of their time reading, trying to understand, reusing and modifying existing source code, rather than writing new source code.