

High-level languages made the process of developing a program simpler and more understandable, and less bound to the underlying hardware. The following properties are among the most important: In computer programming, readability refers to the ease with which a human reader can comprehend the purpose, control flow, and operation of source code. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. They are the building blocks for all software, from the simplest applications to the most sophisticated ones. Normally the first step in debugging is to attempt to reproduce the problem. Trial-and-error/divide-and-conquer is needed: the programmer will try to remove some parts of the original test case and check if the problem still exists. A similar technique used for database design is Entity-Relationship Modeling (ER Modeling). Programmable devices have existed for centuries. However, Charles Babbage had already written his first program for the Analytical Engine in 1837. Some languages are very popular for particular kinds of applications, while some languages are regularly used to write many different kinds of applications. Their jobs usually involve: Although programming has been presented in the media as a somewhat mathematical subject, some research shows that good programmers have strong skills in natural human languages, and that learning to code is similar to learning a foreign language. Programs were mostly entered using punched cards or paper tape. It affects the aspects of quality above, including portability, usability and most importantly maintainability. The following properties are among the most important: In computer programming, readability refers to the ease with which a human reader can comprehend the purpose, control flow, and operation of source code. Some of these factors include: The presentation aspects of this (such as indents, line breaks, color highlighting, and so on) are often handled by the source code editor, but the content aspects reflect the programmer's talent and skills. Text editors were also developed that allowed changes and corrections to be made much more easily than with punched cards. For this purpose, algorithms are classified into orders using so-called Big O notation, which expresses resource use, such as execution time or memory consumption, in terms of the size of an input. Some languages are very popular for particular kinds of applications, while some languages are regularly used to write many different kinds of applications. Assembly languages were soon developed that let the programmer specify instruction in a text format (e.g., ADD X, TOTAL), with abbreviations for each operation code and meaningful names for specifying addresses. Readability is important because programmers spend the majority of their time reading, trying to understand, reusing and modifying existing source code, rather than writing new source code. They are the building blocks for all software, from the simplest applications to the most sophisticated ones. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. He gave the first description of cryptanalysis by frequency analysis, the earliest code-breaking algorithm. Sometimes software development is known as software engineering, especially when it employs formal methods or follows an engineering design process. Debugging is a very important task in the software development process since having defects in a program can have significant consequences for its users.