

A similar technique used for database design is Entity-Relationship Modeling (ER Modeling). Unreadable code often leads to bugs, inefficiencies, and duplicated code. There exist a lot of different approaches for each of those tasks. In the 1880s, Herman Hollerith invented the concept of storing data in machine-readable form. Computer programming or coding is the composition of sequences of instructions, called programs, that computers can follow to perform tasks. As early as the 9th century, a programmable music sequencer was invented by the Persian Banu Musa brothers, who described an automated mechanical flute player in the Book of Ingenious Devices. While these are sometimes considered programming, often the term software development is used for this larger overall process – with the terms programming, implementation, and coding reserved for the writing and editing of code per se. Various visual programming languages have also been developed with the intent to resolve readability concerns by adopting non-traditional approaches to code structure and display. Compilers harnessed the power of computers to make programming easier by allowing programmers to specify calculations by entering a formula using infix notation. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. Text editors were also developed that allowed changes and corrections to be made much more easily than with punched cards. Use of a static code analysis tool can help detect some possible problems. Trade-offs from this ideal involve finding enough programmers who know the language to build a team, the availability of compilers for that language, and the efficiency with which programs written in a given language execute. One approach popular for requirements analysis is Use Case analysis. Normally the first step in debugging is to attempt to reproduce the problem. The first compiler related tool, the A-0 System, was developed in 1952 by Grace Hopper, who also coined the term 'compiler'. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. Many factors, having little or nothing to do with the ability of the computer to efficiently compile and execute the code, contribute to readability. The choice of language used is subject to many considerations, such as company policy, suitability to task, availability of third-party packages, or individual preference. Some of these factors include: The presentation aspects of this (such as indents, line breaks, color highlighting, and so on) are often handled by the source code editor, but the content aspects reflect the programmer's talent and skills. It is usually easier to code in "high-level" languages than in "low-level" ones. Whatever the approach to development may be, the final program must satisfy some fundamental properties. A similar technique used for database design is Entity-Relationship Modeling (ER Modeling). Debugging is a very important task in the software development process since having defects in a program can have significant consequences for its users. Methods of measuring programming language popularity include: counting the number of job advertisements that mention the language, the number of books sold and courses teaching the language (this overestimates the importance of newer languages), and estimates of the number of existing lines of code written in the language (this underestimates the number of users of business languages such as COBOL).