

Later a control panel (plug board) added to his 1906 Type I Tabulator allowed it to be programmed for different jobs, and by the late 1940s, unit record equipment such as the IBM 602 and IBM 604, were programmed by control panels in a similar way, as were the first electronic computers. Programmable devices have existed for centuries. Expert programmers are familiar with a variety of well-established algorithms and their respective complexities and use this knowledge to choose algorithms that are best suited to the circumstances. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. Debugging is often done with IDEs. Standalone debuggers like GDB are also used, and these often provide less of a visual environment, usually using a command line. Sometimes software development is known as software engineering, especially when it employs formal methods or follows an engineering design process. A similar technique used for database design is Entity-Relationship Modeling (ER Modeling). By the late 1960s, data storage devices and computer terminals became inexpensive enough that programs could be created by typing directly into the computers. As early as the 9th century, a programmable music sequencer was invented by the Persian Banu Musa brothers, who described an automated mechanical flute player in the Book of Ingenious Devices. Auxiliary tasks accompanying and related to programming include analyzing requirements, testing, debugging (investigating and fixing problems), implementation of build systems, and management of derived artifacts, such as programs' machine code. Proficient programming usually requires expertise in several different subjects, including knowledge of the application domain, details of programming languages and generic code libraries, specialized algorithms, and formal logic. In the 9th century, the Arab mathematician Al-Kindi described a cryptographic algorithm for deciphering encrypted code, in A Manuscript on Deciphering Cryptographic Messages. High-level languages made the process of developing a program simpler and more understandable, and less bound to the underlying hardware. In 1801, the Jacquard loom could produce entirely different weaves by changing the "program" – a series of pasteboard cards with holes punched in them. Unreadable code often leads to bugs, inefficiencies, and duplicated code. High-level languages made the process of developing a program simpler and more understandable, and less bound to the underlying hardware. Methods of measuring programming language popularity include: counting the number of job advertisements that mention the language, the number of books sold and courses teaching the language (this overestimates the importance of newer languages), and estimates of the number of existing lines of code written in the language (this underestimates the number of users of business languages such as COBOL). Ideally, the programming language best suited for the task at hand will be selected. Following a consistent programming style often helps readability. Some text editors such as Emacs allow GDB to be invoked through them, to provide a visual environment. For this purpose, algorithms are classified into orders using so-called Big O notation, which expresses resource use, such as execution time or memory consumption, in terms of the size of an input. Programs were mostly entered using punched cards or paper tape. The first step in most formal software development processes is requirements analysis, followed by testing to determine value modeling, implementation, and failure elimination (debugging). Various visual programming languages have also been developed with the intent to resolve readability concerns by adopting non-traditional approaches to code structure and display. By the late 1960s, data storage devices and computer terminals became inexpensive enough that programs could be created by typing directly into the computers.