

Allen Downey, in his book *How To Think Like A Computer Scientist*, writes: Many computer languages provide a mechanism to call functions provided by shared libraries. Text editors were also developed that allowed changes and corrections to be made much more easily than with punched cards. Ideally, the programming language best suited for the task at hand will be selected. Expert programmers are familiar with a variety of well-established algorithms and their respective complexities and use this knowledge to choose algorithms that are best suited to the circumstances. Expert programmers are familiar with a variety of well-established algorithms and their respective complexities and use this knowledge to choose algorithms that are best suited to the circumstances. In 1801, the Jacquard loom could produce entirely different weaves by changing the "program" – a series of pasteboard cards with holes punched in them. Some languages are very popular for particular kinds of applications, while some languages are regularly used to write many different kinds of applications. A study found that a few simple readability transformations made code shorter and drastically reduced the time to understand it. The first step in most formal software development processes is requirements analysis, followed by testing to determine value modeling, implementation, and failure elimination (debugging). Later a control panel (plug board) added to his 1906 Type I Tabulator allowed it to be programmed for different jobs, and by the late 1940s, unit record equipment such as the IBM 602 and IBM 604, were programmed by control panels in a similar way, as were the first electronic computers. However, readability is more than just programming style. Trade-offs from this ideal involve finding enough programmers who know the language to build a team, the availability of compilers for that language, and the efficiency with which programs written in a given language execute. Debugging is often done with IDEs. Standalone debuggers like GDB are also used, and these often provide less of a visual environment, usually using a command line. Code-breaking algorithms have also existed for centuries. Normally the first step in debugging is to attempt to reproduce the problem. Debugging is often done with IDEs. Standalone debuggers like GDB are also used, and these often provide less of a visual environment, usually using a command line. While these are sometimes considered programming, often the term software development is used for this larger overall process – with the terms programming, implementation, and coding reserved for the writing and editing of code per se. Later a control panel (plug board) added to his 1906 Type I Tabulator allowed it to be programmed for different jobs, and by the late 1940s, unit record equipment such as the IBM 602 and IBM 604, were programmed by control panels in a similar way, as were the first electronic computers. Programs were mostly entered using punched cards or paper tape. The academic field and the engineering practice of computer programming are both largely concerned with discovering and implementing the most efficient algorithms for a given class of problems. In 1206, the Arab engineer Al-Jazari invented a programmable drum machine where a musical mechanical automaton could be made to play different rhythms and drum patterns, via pegs and cams. This can be a non-trivial task, for example as with parallel processes or some unusual software bugs. Computer programmers are those who write computer software. Scripting and breakpointing is also part of this process. Allen Downey, in his book *How To Think Like A Computer Scientist*, writes: Many computer languages provide a mechanism to call functions provided by shared libraries.