

Unreadable code often leads to bugs, inefficiencies, and duplicated code. By the late 1960s, data storage devices and computer terminals became inexpensive enough that programs could be created by typing directly into the computers. Different programming languages support different styles of programming (called programming paradigms). Programmable devices have existed for centuries. Some text editors such as Emacs allow GDB to be invoked through them, to provide a visual environment. Languages form an approximate spectrum from "low-level" to "high-level"; "low-level" languages are typically more machine-oriented and faster to execute, whereas "high-level" languages are more abstract and easier to use but execute less quickly. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. Also, specific user environment and usage history can make it difficult to reproduce the problem. Normally the first step in debugging is to attempt to reproduce the problem. Computer programming or coding is the composition of sequences of instructions, called programs, that computers can follow to perform tasks. He gave the first description of cryptanalysis by frequency analysis, the earliest code-breaking algorithm. Sometimes software development is known as software engineering, especially when it employs formal methods or follows an engineering design process. Programmers typically use high-level programming languages that are more easily intelligible to humans than machine code, which is directly executed by the central processing unit. For this purpose, algorithms are classified into orders using so-called Big O notation, which expresses resource use, such as execution time or memory consumption, in terms of the size of an input. By the late 1960s, data storage devices and computer terminals became inexpensive enough that programs could be created by typing directly into the computers. Code-breaking algorithms have also existed for centuries. Programmers typically use high-level programming languages that are more easily intelligible to humans than machine code, which is directly executed by the central processing unit. For example, when a bug in a compiler can make it crash when parsing some large source file, a simplification of the test case that results in only few lines from the original source file can be sufficient to reproduce the same crash. However, readability is more than just programming style. He gave the first description of cryptanalysis by frequency analysis, the earliest code-breaking algorithm. The first compiler related tool, the A-0 System, was developed in 1952 by Grace Hopper, who also coined the term 'compiler'. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. Some text editors such as Emacs allow GDB to be invoked through them, to provide a visual environment. In 1206, the Arab engineer Al-Jazari invented a programmable drum machine where a musical mechanical automaton could be made to play different rhythms and drum patterns, via pegs and cams. Programmers typically use high-level programming languages that are more easily intelligible to humans than machine code, which is directly executed by the central processing unit.