

The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. Also, specific user environment and usage history can make it difficult to reproduce the problem. While these are sometimes considered programming, often the term software development is used for this larger overall process – with the terms programming, implementation, and coding reserved for the writing and editing of code per se. These compiled languages allow the programmer to write programs in terms that are syntactically richer, and more capable of abstracting the code, making it easy to target varying machine instruction sets via compilation declarations and heuristics. When debugging the problem in a GUI, the programmer can try to skip some user interaction from the original problem description and check if remaining actions are sufficient for bugs to appear. In the 1880s, Herman Hollerith invented the concept of storing data in machine-readable form. It affects the aspects of quality above, including portability, usability and most importantly maintainability. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. Ideally, the programming language best suited for the task at hand will be selected. Later a control panel (plug board) added to his 1906 Type I Tabulator allowed it to be programmed for different jobs, and by the late 1940s, unit record equipment such as the IBM 602 and IBM 604, were programmed by control panels in a similar way, as were the first electronic computers. Text editors were also developed that allowed changes and corrections to be made much more easily than with punched cards. It affects the aspects of quality above, including portability, usability and most importantly maintainability. Computer programming or coding is the composition of sequences of instructions, called programs, that computers can follow to perform tasks. These compiled languages allow the programmer to write programs in terms that are syntactically richer, and more capable of abstracting the code, making it easy to target varying machine instruction sets via compilation declarations and heuristics. Assembly languages were soon developed that let the programmer specify instruction in a text format (e.g., ADD X, TOTAL), with abbreviations for each operation code and meaningful names for specifying addresses. Ideally, the programming language best suited for the task at hand will be selected. There exist a lot of different approaches for each of those tasks. Expert programmers are familiar with a variety of well-established algorithms and their respective complexities and use this knowledge to choose algorithms that are best suited to the circumstances. As early as the 9th century, a programmable music sequencer was invented by the Persian Banu Musa brothers, who described an automated mechanical flute player in the Book of Ingenious Devices. When debugging the problem in a GUI, the programmer can try to skip some user interaction from the original problem description and check if remaining actions are sufficient for bugs to appear. As early as the 9th century, a programmable music sequencer was invented by the Persian Banu Musa brothers, who described an automated mechanical flute player in the Book of Ingenious Devices. However, readability is more than just programming style. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages.